




M23 servo cable

specification: 6FX8002-5CA05-1AD5

Power cable for SINAMICS S120 and Motors with M23 connection
The resistance to aggressive media should be individually tested for your application. Further details on request.
Female straight – male straight
M23 – M23, 6-pole
4-pole used
shielded
without brake wires
without cable sleeves
Further cable lengths on request.
Plastic housings with good resistance against chemicals and oils.

Link to Product

Illustration



Product may differ from Image

Form

Form PS105

Technical Data

Operating voltage max. 630 V AC/DC

Rated surge voltage	6.0 kV
Operating current per contact	Power cores: 12 A (1.5 mm ²), 15 A (2.5 mm ²)
Material group	IEC 60664-1, category I
Locking of ports	Screw thread (M23×1 mm) recommended torque 2.0 Nm, self-securing
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)
Material	PUR
Locking material	Brass, nickel plated
suitable for corrugated tube (internal Ø)	16 mm; 23 mm
Compression gland	M23 (SW27)

General data

Pollution Degree	3
Temperature range	-25...+85 °C, depending on cable quality

Cables

No./diameter of wires	(4G1.5+C)
Wire isolation	TPM (bk num, gnye)
C-track properties	10 Mio.
Outer Ø	9.1 mm ±5%
Cable number	854
Approval (cable)	cURus (AWM-Style 21223/10492)
Shield	yes
Jacket Color	orange
Temperature range (fixed)	-30...+80 °C
Temperature range (mobile)	-30...+60 °C
Bend radius (fixed)	5× outer Ø
Bend radius (moving)	7.5× outer Ø
Torsion stress	±30°/m
Material (jacket)	PUR (UL/CSA) (=MC800+)
Product article number of manufacturer	7000-PS105-8540350
Cable length	3,5 m