QO48M60DSGP

Generator panel, QO, 1 phase, 4 spaces, 8 circuits, 60A main breaker with interlock, NEMA1, surface cover door, UL



Main

| Marketing Trade Name | QO | |
|----------------------|-------------------------|--|
| Product Type | Panel | |
| Cover Type | Surface cover with door | |

Complementary

| Complementary | | | | |
|--|------------------------------------|--|--|--|
| Tightening Torque | Cover 20 lb.in | | | |
| Load Center Type | Main breaker | | | |
| Rated Current | 60 A | | | |
| Number of Spaces | 4 | | | |
| Max Short Circuit Current Rating | 10 kA | | | |
| Maximum Number of Single Pole Circuits | 8 | | | |
| Maximum Number of Tandem Breakers | 4 | | | |
| Number of Phases | 1 phase | | | |
| Wire Size | AWG 8AWG 2 aluminium/copper | | | |
| Ground Bar | Grounding bar (ordered separately) | | | |
| Electrical Connection | Lugs | | | |
| Wiring Configuration | 3-wire | | | |
| Busbar Material | Tin plated aluminium busbar | | | |
| Enclosure Material | Welded sheet steel | | | |
| Surface Finish | Baked enamel Gray | | | |
| Box Number | 4 | | | |
| Height | 12.56 in (319 mm) | | | |
| Width | 8.90 in (226 mm) | | | |
| | | | | |

Environment

| Enclosure Rating | NEMA 1 indoor | |
|---------------------------------------|---------------------------------|--|
| Ambient Air Temperature for Operation | 23 °F (-5 °C) 104 °F (40 °C) | |
| Product Certifications | UL Listed | |

Ordering and shipping details

| Category | 00101 - QO 1PH LC,2-8CKT,NEMA 1,3R | | | |
|-----------------------|------------------------------------|-----------------------|--|--|
| Discount Schedule | DE3A | DE3A | | |
| GTIN | 00785901824343 | | | |
| Nbr. of units in pkg. | 1 | | | |
| Package weight(Lbs) | 9.45 lb(US) (4.29 kg) | 9.45 lb(US) (4.29 kg) | | |
| Returnability | Yes | | | |
| Country of origin | MX | | | |

Packing Units

| Unit Type of Package 1 | PCE 14.40 in (36.576 cm) 4.70 in (11.938 cm) 10.70 in (27.178 cm) PAL 78 785.00 lb(US) (356.07 kg) 40.00 in (101.6 cm) | |
|------------------------------|--|--|
| Package 1 Height | | |
| Package 1 width | | |
| Package 1 Length | | |
| Unit Type of Package 2 | | |
| Number of Units in Package 2 | | |
| Package 2 Weight | | |
| Package 2 Height | | |
| Package 2 width | 40.00 in (101.6 cm) | |
| Package 2 Length | 48.00 in (121.92 cm) | |
| | | |


Offer Sustainability

| WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov | | |
|---|--|--|
| REACh Declaration | | |
| Yes | | |
| Compliant EEU RoHS Declaration | | |
| Yes | | |
| Yes | | |
| ₫Yes | | |
| ☐ China RoHS Declaration | | |
| | | |

Contractual warranty

| Warranty | 18 months |
|----------|-----------|
| ranany | To months |
| | |

Approximate Dimensions



| KNOCKOUTS | | | | |
|-----------|-----|------|------|------|
| SYMBOL | Α | В | С | D |
| IN | .50 | . 75 | 1.00 | 1.25 |
| MM | 13 | 19 | 25 | 32 |

Connections and Wiring Diagrams

