The Eaton difference



- Built-in patented wire stripper provides handy backup for misplaced tools
- Longer, wider strap provides 40% more contact area to wallboard, virtually eliminating floating installations
- Ultrasonic welded thermoplastic top and bottom housing eliminate call-backs due to job-site breakage
- Cam action mechanism inside for quiet switch action
- Built-in wire looper to speed termination of both #14 and #12 AWG wire
- Slotted, Phillips and Robertson tri-combo screw heads offer greater installation flexibility



Specific switch solutions for today's needs



Aesthetic upgrades

Complete the look of a beautiful redecoration, renovation or new home with decorator switches that provide contemporary styling to coordinate perfectly with today's décor.

See page B-4



Shown: 7503



Device locator lighting

There are areas in every home where it is difficult to visually locate a switch in low-light or dark conditions. Lighted switches emit a soft glow that makes them easy to find without fumbling.

See page B-6



Shown: 1301-7LT

Shown:

5221-7



Aluminum wiring

There are many homes that still contain aluminum wiring. Hybrid copper & aluminum compatible (CO/ALR) switches are required for aluminum wiring.



See page B-7

Product description

Single-pole, 3-way, 4-way 15A, 120/277V/AC

Design features

• Thermoplastic rocker, top and backbody are virtually unbreakable, promising years of durable performance

Decorator standard grade switches

- Ultrasonic welding and integrated construction of the strap and body provide superior integrity
- · Backwire clamps on the side terminals provide for easy installation of #12 and #14 AWG wire
- Push-in terminals accept #14 AWG solid wire
- Stippled ground screw terminal standard

- 120/277V/AC rating ideal for fluorescent lighting fixtures and a broad variety of applications
- Long, broad mounting strap virtually eliminates floating installations
- Patented built-in wire stripper for #12 and #14 AWG wire to speed installation
- Tri-combo screws accept Slotted, Phillips, and Robertson-head tools for installation flexibility
- Lighted switches glow in "OFF" position

Decorator switches



Catalog no.	
□ 7501	• •
□ 7501-9	• •
□ 7503	• •
□ 7503-9	• •
□ 7504*	•
□ 7511	
□ 7513	

cULus Listed to UL20, file no. E18704; 7504 also UL Listed to Federal Spec WS-896E *Fed Spec.

AC decorator switches, back & side wire





Ra	nting				
Α	V/AC	Description	Color	Catalog no.	RoHS
15	120/277	Single-pole, two position, momentary contact, decorator	W	□7521W	•

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), V (Ivory), W (White)



Dimensional information: B-68 Specification information: Please visit www.eaton.com/wiringdevices Compliances, specifications and availability are subject to change without notice.




Indicates NAFTA compliant - Page G-21



B-4

Switches

Family	Α	В	С	D	E
Decorator standard grade, single-pole & 3-way	1.44" (36.6mm)	3.81" (96.8mm)	3.28" (83.3mm)	2.74" (69.6mm)	0.97" (24.6mm)
Decorator standard grade, 4-way	1.44" (36.6mm)	3.81" (96.8mm)	3.28" (83.3mm)	2.60" (66.1mm)	1.38" (35.1mm)
Heavy duty grade toggle	1.31" (33.3mm)	3.28" (83.3mm)	2.38" (60.5mm)	2.00" (50.8mm)	1.05" (26.7mm)
Standard grade toggle	1.31" (33.3mm)	3.28" (83.3mm)	2.38" (60.5mm)	2.13" (54.1mm)	0.88" (22.4mm)
Standard grade toggle, less ears	0.75" (19.1mm)	3.28" (83.3mm)	2.38" (60.5mm)	2.13" (54.1mm)	0.88" (22.4mm)
CO/ALR standard grade toggle	1.31" (33.3mm)	3.28" (83.3mm)	2.38" (60.5mm)	2.13" (54.1mm)	0.88" (22.4mm)



Circuit control switches

Catalog no.	Α	В	C
452	0.50"	0.88"	0.53"
	(12.7mm)	(22.4mm)	(13.5mm)




Feed-through cord switches

Catalog no.	Α	В	С
410	1.35"	0.91"	0.55"
	(34.5mm)	(23.1mm)	(14.0mm)
933	2.49"	1.47"	1.25"
	(63.4mm)	(36.7mm)	(31.6mm)



Combination devices

Family	Α	В	C	D	E
Decorator combination	1.30"	3.81"	3.28"	2.65"	1.08"
	(33.0mm)	(96.8mm)	(83.3mm)	(67.3mm)	(27.4mm)
Traditional combination	1.30"	4.19"	3.28"	2.65"	1.08"
	(33.0mm)	(106.4mm)	(83.3mm)	(67.3mm)	(27.4mm)
Nightlight combination	1.30"	3.81"	3.28"	2.65"	1.08"
	(33.0mm)	(96.8mm)	(83.3mm)	(67.3mm)	(27.4mm)



Duplex receptacle

Family or Catalog no.	Α	В	C	D	E
Heavy duty grade tamper resistant	1.24"	4.00"	3.23"	2.63"	1.04"
	(31.5mm)	(101.6mm)	(82.0mm)	(66.8mm)	(26.4mm)
Decorator standard grade	1.30"	3.81"	3.28"	2.12"	0.69"
	(33.0mm)	(96.8mm)	(83.3mm)	(53.8mm)	(17.5mm)
Standard grade, except 298	1.31"	4.19"	3.28"	2.63"	0.69"
	(33.3mm)	(106.4mm)	(83.3mm)	(66.8mm)	(17.5mm)
298	1.31"	4.19"	3.28"	2.63"	0.74"
	(33.3mm)	(106.4mm)	(83.3mm)	(66.8mm)	(18.8mm)
CO/ALR standard grade	1.38"	4.06"	3.28"	2.61"	0.71"
	(35.1mm)	(103.1mm)	(83.3mm)	(66.3mm)	(18.0mm)

