

Standard grade toggle switches

Product description

Single-pole, 3-way, 4-way
15A, 120V/AC

Design features

- 3-way switches feature additional push-in common termination for feed-through tapping
- Push-in terminals accept #14 AWG solid wire only; side wire terminals accept up to #10 AWG solid wire
- Long, broad mounting strap virtually eliminates floating installations

- Patented built-in wire stripper for #12 and #14 AWG wire to speed installation
- Patented built-in wire looper for pre-looping
- Tri-combo screws accept Slotted, Phillips, and Robertson-head tools for installation flexibility
- Lighted toggle glows in "OFF" position



1303



1301-7



1301-73

Toggle switches, non-grounding 426

Rating		Description	Color suffix	Catalog no.	
15	120	Single-pole, side wire & push wire	B, BK, LA, V, W	<input type="checkbox"/> 1301_	• •
		3-way, back wire, side wire & push wire	B, BK, LA, V, W	<input type="checkbox"/> 1303_	• •

cULus Listed to UL20, file no. E18704; 7504 also UL Listed to Federal Spec WS-896E

Toggle switches, grounding 426

Rating		Description	Color suffix	Catalog no.	
15	120	Single-pole, side wire & push wire	A, B, BK, LA, V, W	<input type="checkbox"/> 1301-7_	• •
		Single-pole, side wire & push wire, auto ground	A, B, BK, LA, V, W	<input type="checkbox"/> 1301-9_	• •
		3-way, back wire, side wire & push wire	A, B, BK, LA, V, W	<input type="checkbox"/> 1303-7_	• •
		3-way, side wire & push wire, auto ground	A, B, BK, LA, V, W	<input type="checkbox"/> 1303-9_	• •
		4-way, side wire & push wire	A, B, BK, LA, V, W	<input type="checkbox"/> 1242-7_	
		Single-pole, less ears, side wire & push wire	A, B, BK, LA, W	<input type="checkbox"/> 1301-73_	• •
		Lighted, single-pole, side wire & push wire	LA, V, W	<input type="checkbox"/> 1301-7LT_	•
		Lighted, 3-way, side wire & push wire	V, W	<input type="checkbox"/> 1303-7LT_	•

cULus Listed to UL20, file no. E18704; NOM certified. Lighted models also CSA certified to C22.2, no. 111

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), LA (Light Almond), V (Ivory), W (White)

A (Almond)	B (Brown)	BK (Black)	LA (Lt. Almond)	V (Ivory)	W (White)
----------------------	---------------------	----------------------	---------------------------	---------------------	---------------------

Dimensional information: B-68 Specification information: Please visit www.eaton.com/wiringdevices
Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page G-21

RoHS compliant - Page G-21