Blank and Custom Engraved Legend Plates

Style	Color	Small Catalog Number	Standard Catalog Number	Jumbo ① Catalog Number	Extra Large ② Catalog Number	Four-Position Sel Custom ^③ Catalog Number	ector Switch Standard Catalog Number	Push-Pull with Sy Standard Catalog Number	rmbols ⁴ Jumbo ¹⁾ Catalog Number
Square ®	Black	10250TMS36	10250TS36	10250TL36	_	10250TS76	10250TS72	10250TPP17	10250TPP18
	Red	10250TMS37	10250TS37	10250TL37	_	_	_	_	_
	Green/red	_	_	_	_	_	_	10250TPP20	10250TPP21
	Satin alum.	_	_	_	10250TNP99	_	_	_	_
1/2 Round	Black	10250TP36	10250TM36	10250TJ36	_	_	10250TM72	10250TR17	10250TR18
	Red	10250TP37	10250TM37	10250TJ37	_	_	_	_	_
	Green/red	_	_	_	_	_	_	10250TR20	10250TR21
	Satin alum.	_	10250TM89	10250TJ89	_	_	_	_	_

Notes

- $^{\scriptsize \textcircled{\tiny 1}}$ Cannot be used on cast enclosures except for top row. Suitable for most sheet metal enclosures.
- ^② When used to meet Ford Motor Co. specifications, specify engraved legend. Cannot be used on standard cast or sheet metal enclosures.
- ${\small \footnotesize \textbf{③} \ \ \, Slightly larger than standard size for legends requiring more space—fits cast enclosures.} \\$
- $^{\textcircled{4}}$ All push-pull legend plates include the symbols $\neq \emptyset$ in the center of the plate.
- © Square legend plates have a satin aluminum field. Color is on lower portion.

Pushbutton and Pilot Devices

Accessories

Accessories

Fingerproof Shroud 10 per package Fits new style contact blocks and light units.

10250TA101

	Accessories				
	Description	Catalog Number		Description	Catalog Number
	Padlock Attachments			Boots	
10250TA2	Padlocking Attachment for Flush Pushbutton Operators Permits locking NC contacts in open position with 1/4 in padlock. Will not lock NO contact		10250TA_	Flexible Weather Resistant Boot For use with button operators (extended buttons preferred). Temperature to -25°F (-32°C). (See Page V9-T4-48 for 10250TA96	
10250TA26	Padlocking Attachment for Use with Extended Pushbutton Permits locking NC contacts in open position	10250TA26		Tightening Tool.) Black Red	10250TA3 10250TA4 ①
	with 1/4 in padlock.			Green	10250TA10
10250TA36	Padlocking Cover Guard Cover locked over flush button makes it unaccessible or on extended button locks NC contacts open. Takes 1/4 in shank size padlock.	10250TA36	10250TA25	Transparent Boot For regular illuminated pushbutton operators and PresTest—Temperature to −38°F (−39°C). ②	10250TA25
10250TA38	Padlock Hasp or Flip-Up Guard	10250TA38	10250TA4_	Boot for Flush Pushbutton	
	When used with a 1/4 in padlock, makes flush and long button and knob selector switch		100	Clear	10250TA46
	unaccessible, but not locked down. Without			Black	10250TA47
1	the padlock, it is a flip-up guard. Padlock hasp			Red	10250TA48
	can be removed before assembly.			Green	10250TA49
10250TA63	Padlocking Attachment for Use with Flexible Weather Resistant Boot	10250TA63		Hardware and Kits	
	Used on long button operators. Stainless steel. Use only for locking NC contacts open.		10250TK3	Thrust Washers To meet Ford Motor Co. mounting specifications.	10250TK3
10250TA64	Padlock Attachment For use with illuminated pushbuttons and maintained push-pull operators having standard button or lens only. Use 1/4 in padlock. Locks in down position only.	10250TA64	10250TK5	Contact Block Tape Seal Seals plunger openings on last contact block. Order in multiples of 10 pieces.	10250TK5
10250TA11	Padlocking Attachment for Non- Illuminated Knob Selector Switches Provision for up to 5, 1/4 in padlocks.	10250TA11	56-9337	Selector Switch Operator Gasket Seals out dust from getting in between the cam and contact block plungers. Supplied as standard with all selector switches.	56-9337
	Shrouds and Guards				
10250TA6	Shroud for Mushroom Head Operator Prevents accidental operation. (Not for push-pull operators.)	10250TA6	10250TA3_	Special Retaining Nut To accommodate thick panel: Indicating lights PresTest, pushbuttons and selector switches	10250TA30
3/1				Trestest, pushbuttons and selector switches	102301A31
10250TA12	Extended Retaining Nut Replaces standard nut and provides guard for flush head pushbutton operators.	10250TA12	10250TA62	Terminal Block Two terminals, each will accommodate two wire terminations.	10250TA62
10250TA15	Guard for Illuminated Pushbutton	10250TA15	400E0TA0	Canada Birar	10250742
033			10250TA8	Spacer Ring Used when legend plate is not required.	10250TA8
10250TA56_	Shroud		4000077	Otracking Communication	400507470
	For jumbo mushroom head operator. Gray Yellow	10250TA56 10250TA56Y	10250TA79	Stacking Screw Replaces transformer mounting screws on indicating light so terminal block 10250TA62 can be mounted to light to support and connect a series resistor. This screw also fits	10250TA79
10250ED1241	Half Shroud—Yellow	10250ED1241		all contact blocks. Order in multiples of 10.	
0	For jumbo mushroom head operator.		Notes ① Should not be use	d on flush button for STOP function.	

 $\ensuremath{@}$ Not suitable for single contact block depth cast enclosure. Cover is too thick.