

Wallplate families

Rugged design and quality materials make Arrow Hart wallplates the best choice

Whether faced with a commercial, institutional or industrial setting, you will find the desired material, configuration, style, size and color you need



Standard size

Wallplates for precision cuts




Mid-size and oversize

Wallplates for applications that require additional wall coverage



Extra depth

Wallplates to provide a flush fit to the wall when an old work outlet box is used



Specification grade thermoplastic

- Available in both nylon and polycarbonate constructions
- Virtually unbreakable plates reduce installation and replacement costs
- Preferred for industrial, institutional, and other high-traffic areas
- Exclusive time-saving screw catch feature holds mounting screws captive and simplifies installation
- High gloss finish is soil-resistant
- Available in standard size and mid-size configurations with screwless and pre-marked special use versions available




Specification grade metal wallplates

- Constructed of non-corrosive 302/304 Stainless steel, brass or chrome
- Available in standard, mid-size, and oversize configurations with pre-marked special use versions available
- 302/304 Stainless steel is non-magnetic and non-corrosive for rugged durability
- Solid brass is coated with transparent lacquer to resist premature oxidation
- Shipped with removable protective film
- Recommended for industrial, institutional and commercial applications


Wallplate dimensional information

Mounting holes for wallplates and covers


These are the most common nominal spacings for mounting holes on wallplates and covers. Holes are normally countersunk for oval head #6-32 screws.




Device or strap



Box




Decorator/GFCI




FS box

Cover opening dimensions


Nominal dimensions for cover openings conform to industry standards and practices.



4-wire power device



Off center power device



3-wire power device




Single locking receptacle 20/30 amp




Single receptacle

Plate opening dimensions


Nominal dimensions for plate openings conform to industry standards and practices.



Toggle



Decorator




Duplex receptacle


Wallplate sizes

Gang	Description	Height	Width	First gang to edge	Gang to gang
1-Gang	Standard	4.50" (114.3mm)	2.75" (69.8mm)	1.37" (34.9mm)	—
	Mid-size	4.87" (123.8mm)	3.12" (79.4mm)	1.56" (39.7mm)	—
	Oversize	5.25" (133.3mm)	3.50" (88.9mm)	1.75" (44.4mm)	—
2-Gang	Standard	4.50" (114.3mm)	4.56" (115.9mm)	1.37" (34.9mm)	1.81" (46.0mm)
	Mid-size	4.87" (123.8mm)	4.94" (125.4mm)	1.56" (39.7mm)	1.81" (46.0mm)
	Oversize	5.25" (133.3mm)	5.31" (134.9mm)	1.75" (44.4mm)	1.81" (46.0mm)
3-Gang	Standard	4.50" (114.3mm)	6.37" (161.9mm)	1.37" (34.9mm)	1.81" (46.0mm)
	Mid-size	4.87" (123.8mm)	6.75" (171.4mm)	1.56" (39.7mm)	1.81" (46.0mm)
	Oversize	5.25" (133.3mm)	7.17" (182.2mm)	1.75" (44.4mm)	1.81" (46.0mm)
4-Gang	Standard	4.50" (114.3mm)	8.19" (207.9mm)	1.37" (34.9mm)	1.81" (46.0mm)
	Mid-size	4.87" (123.8mm)	8.56" (217.5mm)	1.56" (39.7mm)	1.81" (46.0mm)
	Oversize	5.25" (133.3mm)	8.94" (227.0mm)	1.75" (44.4mm)	1.81" (46.0mm)
5-Gang	Standard	4.50" (114.3mm)	10.00" (254.0mm)	1.37" (34.9mm)	1.81" (46.0mm)
	Mid-size	4.87" (123.8mm)	10.37" (263.5mm)	1.56" (39.7mm)	1.81" (46.0mm)
6-Gang	Standard	4.50" (114.3mm)	11.81" (300.0mm)	1.37" (34.9mm)	1.81" (46.0mm)
	Mid-size	4.87" (123.8mm)	12.18" (309.5mm)	1.56" (39.7mm)	1.81" (46.0mm)


Standard




Mid-size



Oversize Mid-size Standard




Oversize




Standard size duplex receptacle wallplates

Product description


1-Gang, 2-Gang, 3-Gang




1-Gang



2-Gang





3-Gang



1-Gang

Duplex receptacle



Gang	Material	Color suffix	Catalog no.		
1-Gang	Nylon	A, B, BK, GY, LA, RD, V, W	□ 5132__	•	•
	Thermoset	A, B, LA, V, W	□ 2132__	•	•
	302/304 Stainless steel	—	□ 93101	•	•
	Brass	—	□ 94101	•	•
2-Gang	Nylon	A, B, BK, GY, LA, RD, V, W	□ 5150__	•	•
	Thermoset	A, B, LA, V, W	□ 2150__	•	•
	302/304 Stainless steel	—	□ 93102	•	•
	Brass	—	□ 94102	•	•
3-Gang	302/304 Stainless steel	—	□ 93103	•	•

Standard size single receptacle wallplates

Product description











1-Gang

Single receptacle

Gang	Material	Color suffix	Catalog no.		
1-Gang with 1.406" (35.712mm) hole	Nylon	A, B, BK, GY, RD, V, W	□ 5131__	•	•
	Thermoset	A, B, LA, V, W	□ 2131__	•	•
	302/304 Stainless steel	—	□ 93091	•	•
	Brass	—	□ 94091	•	•

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), RD (Red), V (Ivory), W (White)

							
A (Almond)	B (Brown)	BK (Black)	GY (Gray)	LA (Lt. Almond)	RD (Red)	V (Ivory)	W (White)
							
(Stainless Steel)	(Brass)						

Certification information: 2000, 4000, 5000, ST & PJ series wallplates are cULus Listed; 93000 series wallplates are UL Listed and CSA Certified; 94000 series are UL Listed and CSA certified. **Specification information:** K-22

Compliances, specifications and availability are subject to change without notice.

 Indicates NAFTA compliant - Page Q-32

 RoHS compliant - Page Q-32

Wallplate specification & performance data

Wallplates

Product description

Standard size, mid-size, oversize

Wallplate sizes: standard size, mid-sized & oversize wallplates				
Material type	Thermoset	Nylon	Stainless steel	Polycarbonate
Manufacturing process	Injection molded	Injection molded	Stamped	Injection molded
Testing & code compliance	<ul style="list-style-type: none"> • UL Listed to UL 514D, file no. E33216 • cUL Listed to C22.2, no. 42.1, UL file E33216 	<ul style="list-style-type: none"> • UL Listed to UL 514D, file no. E33216 • cUL Listed to C22.2, no. 42.1, UL file E33216 	<ul style="list-style-type: none"> • UL Listed to 514D, file no. E92003 • CSA certified to C22.2, no. 42.1 	<ul style="list-style-type: none"> • UL Listed to UL 514D, file no. E33216 • cUL, UL file E33216 certified to C22.2, no. 42.1
Environmental specifications	Flammability: Meets UL94 requirements; 5VA rated Temperature rating: -40°C to 90°C (-40°F to 194°F)	Flammability: Meets UL94 requirements; 5VA rated Temperature rating: -40°C to 70°C (-40°F to 158°F)	Flammability: N/A Temperature rating: -40°C to 70°C (-40°F to 158°F)	Flammability: Meets UL94 requirements; 5VA rated Temperature rating: -40° to 70° C (-40°F to 158°F)
Materials	Body: 0.080" thick thermoset urea or phenolic Inner wallplate: N/A	Body: 0.060" thick thermoplastic Inner wallplate: N/A	Body: 0.032" thick stainless steel alloy, 18% chromium and 8% nickel for corrosion resistance Inner wallplate: N/A	Body: 0.08" thick thermoplastic polycarbonate Inner wallplate: 0.071" thick polycarbonate (PJS Series)

Compliances, specifications and availability are subject to change without notice.