

Rigid and intermediate metal conduit fittings

Conduit spacers for rigid metal conduit, intermediate metal conduit and electrical metal tubing



Used with conduit straps to permit space between conduit and mounting surface. Eliminates need for costly offset-bending conduit and possible corrosive moisture traps when conduit is mounted directly to a surface. Hot-dipped galvanized finish, premountable and stackable to eliminate offsetting.

Pipe spacers



| Diagram | Cat. no. | | Size (in.) | Screw size | Dimensions (in.) | |
|---------|-----------|--------|------------------|------------|------------------|--------|
| | Mal. Iron | Alum. | | | A | B |
| | 1350 | 1350AL | 3/8, 1/2, 3/4, 1 | #7 | 3 | 7/8 |
| | 1351 | 1351AL | 1 1/4-1 1/2-2 | #12 | 5 | 1 3/16 |
| | 1352 | 1352AL | 2 1/2-3 | #12 | 9 9/16 | 1 3/4 |
| | 1353 | 1353AL | 3 1/2-4 | #14 | 7 9/16 | 2 |

Conforms to CEC Rule 12-012 (5)
UL not applicable



Corrosion-resistant PVC-coated malleable iron. Pre-mountable, stackable to eliminate offsetting. Spacers can be stacked for offsets on wall or into outlet box.

Prevents conduit rusting from wall condensation. Eliminates offsetting of conduit.

Pipe spacers – PVC coated



| Diagram | Cat. no. | Conduit size (in.) | Screw size | Dimensions (in.) | |
|---------|----------|--------------------|------------|------------------|-------|
| | | | | A | B |
| | 1350CR | 1/2-3/4-1 | #7 | 3 | 7/8 |
| | 1351CR | 1 1/4-1 1/2-2 | #12 | 5 | 3/8 |
| | 1352CR | 2 1/2-3 | #12 | 6 9/16 | 1 3/4 |
| | 1353CR | 3 1/2-4 | #14 | 7 9/16 | 2 |

Conforms to CEC Rule 12-012 (5)
UL not applicable