

Hubs and bulkhead fittings

Bullet® hubs – steel/malleable iron and aluminum^{*†}



- UL listed rain tight and CSA certified watertight and dust tight
- Available in steel/malleable iron (steel through 1") with nylon-insulated throat – with or without series 106 bonding locknut
- Also available in aluminum without insulated throat
- When used with neoprene O-ring, provides watertight threaded hub on enclosures
- UL Listed 105 °C
- Look for the unique blue color, ensuring the highest quality fitting

Bullet hubs



Cat. no.

Steel/M.I. w/locknut	Alum.**	Steel/M.I. w/bonding locknut	Hub size (in.)	Dimensions (in.)			Max. wall thickness (in.)
				A	B	C	
370	370AL	401	1/2	1 3/8	1 1/4	3/4	5/16
371	371AL	402	3/4	1 5/8	1 1/4	3/4	5/16
372	372AL	403	1	2 3/32	1 3/8	7/8	5/16
373	373AL	404-TB	1 1/8	2 9/16	1 5/8	1	5/16
374	374AL	405	1 1/2	3 3/32	1 5/8	1	5/16
375	375AL	406-TB	2	3 5/8	1 5/8	1	5/16
376	–	407	2 1/2	4 1/8	1 7/8	1 1/8	3/8
377	–	408	3	5	2 1/2	1 1/2	1/2
378	–	409	3 1/2	5 9/16	2 1/2	1 1/2	1/2
379	–	410-TB	4	6 3/16	2 1/2	1 1/2	1/2
381	–	–	5	8	3 1/8	–	1/2
382	–	–	6	9 3/16	3 1/8	–	1/2

* Suitable for hazardous locations use in Class I, Div. 2; Class II, Div. 2; Class III, Div. 1 and 2 where general purpose equipment is specifically permitted per NEC Section 500-2(a).

** Aluminum not available with insulated throat.


† UL listed rain tight and CSA certified watertight and dust tight Available with DURA-PLATE® finish.

UL File No. E-23018

For steel.: CSA File No. 2284

For aluminum.: CSA File No. 0637

Diagram



Spacing chart for Bullet hubs

	Center-to-center spacing conduit sizes (in.)												Min. space from center of Bullet hub to wall of box (in.)	KO diameter min. (in.)
	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	3 1/2	4	5	6		
1/2	1 1/16	1 5/8	1 3/4	2 1/8	2 3/8	2 5/8	2 7/8	3 5/16	3 1/2	3 7/8	4 7/8	5 5/16	3/4	7/8
3/4	–	1 3/4	1 7/8	2 1/4	2 1/2	2 3/4	3	3 1/2	3 3/4	4 1/8	4 13/16	5 1/2	7/8	1 1/8
1	–	–	2	2 3/8	2 5/8	2 7/8	3 1/8	3 5/8	3 7/8	4 1/4	4 15/16	5 11/16	1 1/8	1 3/8
1 1/4	–	–	–	2 11/16	2 15/16	3 1/4	3 1/2	4	4 1/4	4 1/2	5 5/16	5 3/4	1 3/8	1 3/4
1 1/2	–	–	–	–	3 1/8	3 1/2	3 3/4	4 1/8	4 3/8	4 3/4	7 1/16	6 3/16	1 5/8	2
2	–	–	–	–	–	3 3/4	4	4 1/2	4 3/4	5	5 3/4	6 1/2	1 7/8	2 1/2
2 1/2	–	–	–	–	–	–	4 1/4	4 3/4	5	5 3/8	6	6 3/4	2 1/8	3
3	–	–	–	–	–	–	–	5 1/8	5 3/8	5 3/4	6 3/8	7 1/8	2 5/8	3 5/8
3 1/2	–	–	–	–	–	–	–	–	5 5/8	6	6 3/4	7 1/2	2 7/8	4 1/8
4	–	–	–	–	–	–	–	–	–	6 1/4	7 1/8	7 7/8	3 1/4	4 5/8
5	–	–	–	–	–	–	–	–	–	–	8	8 3/4	4	5 1/2
6	–	–	–	–	–	–	–	–	–	–	8 3/4	9 1/2	4 3/4	6 1/2