


PRODUCT-DETAILS

376

2.5 INCH INSUL BULLET CONDUIT HUB



General Information

Extended Product Type	376
Product ID	7TAD013110R0001
EAN	5415022257380
Catalog Description	2.5 INCH INSUL BULLET CONDUIT HUB
Long Description	2-1/2 Inch Hub Connector, Malleable Iron Electro Zinc Plated, Nylon Insulated for Use with Rigid/IMC Conduit

Ordering

EAN	5415022257380
-----	---------------

Dimensions

Product Net Weight	1.86 lb
	843.537 g

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	5 piece
Package Level 2 Width	7 in
	178 mm
Package Level 2 Height	5.2 in

	132 mm
Package Level 2 Depth /	10.8 in
Length	274 mm

Additional Information

Application	To Connect Threaded Metal Conduit to a Threadless Opening in a Box or Enclosure
Brand / Label	T&B Rigid Fittings
Material	Malleable Iron
Number of Batteries	0
Product Name	INSULATED FITTING FOR CONDUIT
Product Type	Hub Connector
Size	2-1/2 Inch
Special Functions	Rain Tight and CSA Certified Watertight and Dust Tight
Standards	UL E23018, CSA
Surface Finishing	Zinc Plated
Temperature Range	UL Listed 105 °C
UPC	786210003764

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	376
Instructions and Manuals	376

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121311
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4441 >> Electrical fittings

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Rigid Cable Protection Systems

