


nVent ERICO Cadweld One Shot, Cable to Ground Rod – GT1161G



- Single use ceramic mold which eliminates the need for a graphite mold and handle clamp/frame
- Produces a permanent connection that will not loosen or corrode
- Fits plain copper-bonded, threaded copper-bonded, full-size galvanized and stainless steel ground rods
- NEC® compliant
- Meets requirements of the Buy American Act



Part Number	GT1161G
Welding Material Type	Traditional
Mold Family	GT (ONE SHOT)
Ground Rod Diameter, Nominal	5/8"
Ground Rod Diameter, Actual	0.555" – 0.635"
Connection, Solid	#8 #6
Connection, Stranded	#8
Certifications	cULus RUS
Standard Packaging Quantity	6 pc
UPC	78285600094

A gap between conductors may be required. See mold tag for more information.

NEC is a registered trademark of, and National Electrical Code (NEC) standard is a copyright of the National Fire Protection Association, Inc. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.