

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12807378

Catalog # : 05018ET3V326T-W22G

Frame : 324/6T
 Output : 50 HP (37 kW)
 Poles : 4
 Frequency : 60 Hz
 Rated voltage : 200/400 V
 Rated current : 136/68.1 A
 L. R. Amperes : 844/422 A
 LRC : 6.2x(Code G)
 No load current : 54.0/27.0 A
 Rated speed : 1775 rpm
 Slip : 1.39 %
 Rated torque : 148 ft.lb
 Locked rotor torque : 229 %
 Breakdown torque : 270 %
 Insulation class : F
 Service factor : 1.25
 Moment of inertia (J) : 9.16 sq.ft.lb
 Design : B

Locked rotor time : 27s (cold) 15s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : -20°C to +40°C
 Altitude : 1000 m.a.s.l.
 Protection degree : IP55
 Cooling method : IC411 - TEFC
 Mounting : F-1
 Rotation¹ : Both (CW and CCW)
 Noise level² : 70.0 dB(A)
 Starting method : Direct On Line
 Approx. weight³ : 596 lb

Output	25%	50%	75%	100%
Efficiency (%)	92.5	93.0	94.1	94.5
Power Factor	0.42	0.66	0.77	0.83

Foundation loads

Max. traction : 1235 lb
 Max. compression : 1831 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
5.7	4.9	4.7	2.7	1.9	1.2	0.9

	Drive end	Non drive end
Bearing type	6312 C3	6212 C3
Sealing	V'Ring	V'Ring
Lubrication interval	20000 h	20000 h
Lubricant amount	21 g	13 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	26/03/2024			
		Revision		