

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium Efficiency
Three-Phase

Product code : 14014004

Catalog # : 00218OT3J145T-S

Frame : 143/5T
Output : 2 HP (1.5 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 380/660 V
Rated current : 3.26/1.87 A
L. R. Amperes : 25.1/14.4 A
LRC : 7.7x(Code K)
No load current : 1.66/0.956 A
Rated speed : 1740 rpm
Slip : 3.33 %
Rated torque : 6.04 ft.lb
Locked rotor torque : 260 %
Breakdown torque : 320 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.1163 sq.ft.lb
Design : B

Locked rotor time : 30s (cold) 17s (hot)
Temperature rise : 70 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +50°C
Altitude : 1000 m.a.s.l.
Cooling method : IC01 - ODP
Mounting : B3R(D)
Rotation¹ : Both (CW and CCW)
Noise level² : 52.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 39.9 lb

Output	25%	50%	75%	100%
--------	-----	-----	-----	------

Efficiency (%)	0.000	85.5	86.5	86.5
Power Factor	0.00	0.61	0.74	0.81

Foundation loads

Max. traction : 148 lb
Max. compression : 188 lb

	Drive end	Non drive end
Bearing type	6205 ZZ	6203 ZZ
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	0 h	0 h
Lubricant amount	0 g	0 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
		Revision		