## **DATA SHEET**

## Three Phase Induction Motor - Squirrel Cage



Customer Product line : Rolled Steel NEMA Premium Efficiency Product code: 12655082 Three-Phase Catalog #: 00236ET3E145T-S Frame : 143/5T Locked rotor time : 23s (cold) 13s (hot) Output : 2 HP (1.5 kW) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) : -20°C to +40°C Frequency : 60 Hz Ambient temperature Rated voltage : 230/460 V : 1000 m.a.s.l. Altitude Rated current : 4.94/2.47 A Protection degree : IP55 L. R. Amperes Cooling method : IC411 - TEFC : 48.9/24.5 A LRC : 9.9x(Code L) Mounting : F-1 No load current : 2.13/1.06 A Rotation<sup>1</sup> : Both (CW and CCW) Rated speed : 3520 rpm Noise level<sup>2</sup> : 68.0 dB(A) Starting method Slip : 2.22 % : Direct On Line Rated torque : 2.98 ft.lb Approx. weight<sup>3</sup> : 40.7 lb Locked rotor torque : 250 % Breakdown torque : 300 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 0.1279 sq.ft.lb Design : B 50% 100% Foundation loads Output 75% 85.5 84.6 85.5 83.3 Efficiency (%) 82.5 84.0 Max. traction : 87 lb 83.3 84.9 84.5 Power Factor 0.73 0.79 0.83 0.88 0.89 0.92 Max. compression : 127 lb 0.73 0.84 0.89 Losses at normative operating points (speed;torque), in percentage of rated output power P1 (0,9;1,0) 15.4 16.7 P2 (0,5;1,0) 10.7 12.6 11.6 P3 (0,25;1,0) 9.4 11.2 10.2 Losses (%) P4 (0,9;0,5) 9.5 11.3 10.3 P5 (0,5;0,5) 4.8 5.7 5.2 P6 (0,5;0,25) 3.5 4.1 3.8 P7 (0,25;0,25) 1.9 2.3 2.1 Drive end Non drive end Bearing type 6205 ZZ 6203 ZZ V'Ring Without Bearing Seal Sealing Lubrication interval Lubricant amount Lubricant type Mobil Polyrex EM Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	26/03/2024			1/1	