DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer

Product line : Rolled Steel NEMA Premium Efficiency

Three-Phase

Product code: 12707693

Catalog #: 01536ET3E254T-S

Frame : 254/6T

Output : 15 HP (11 kW) Poles Frequency : 60 Hz Rated voltage : 230/460 V Rated current : 34.8/17.4 A L. R. Amperes : 237/118 A LRC

: 6.8x(Code G) No load current : 13.0/6.50 A Rated speed : 3525 rpm Slip : 2.08 % Rated torque : 22.3 ft.lb Locked rotor torque : 200 %

Breakdown torque : 300 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 0.8718 sq.ft.lb

Design : B

Locked rotor time

: 25s (cold) 14s (hot) Temperature rise : 80 K Duty cycle : Cont.(S1)

Ambient temperature Altitude

: -20°C to +40°C : 1000 m.a.s.l.

: IP55 Protection degree

Cooling method : IC411 - TEFC

Mounting : F-1

Rotation¹ : Both (CW and CCW) Noise level² : 75.0 dB(A) Starting method : Direct On Line

Approx. weight³ : 188 lb

50% 75% 100% Output Foundation loads

91.0 Efficiency (%) 89.5 91.0 Max. traction : 227 lb Power Factor 0.87 : 415 lb 0.73 0.83 Max. compression

Non drive end Drive end Bearing type 6309 Z C3 6208 Z C3 Sealing V'Ring Without Bearing Seal Lubrication interval 15797 h 20000 h Lubricant amount 8 g 13 g

Lubricant type Mobil Polyrex EM

Notes:

USABLE @208V 38.5A SF 1.00 SFA 38.5A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	26/03/2024				1/1	