DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : Rolled Steel NEMA Premium Efficiency Product line Product code: 12845389 Three-Phase Catalog #: 00236ET3H145TC-S Frame : 143/5TC Locked rotor time : 23s (cold) 13s (hot) Output : 2 HP (1.5 kW) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) : -20°C to +40°C Frequency : 60 Hz Ambient temperature Rated voltage : 575 V : 1000 m.a.s.l. Altitude Rated current : 1.98 A Protection degree : IP55 L. R. Amperes : 19.6 A Cooling method : IC411 - TEFC LRC : 9.9x(Code L) Mounting : F-1 No load current : 0.850 A Rotation¹ : Both (CW and CCW) Rated speed : 3520 rpm Noise level² : 68.0 dB(A) Starting method Slip : 2.22 % : Direct On Line Rated torque : 2.98 ft.lb Approx. weight³ : 40.9 lb Locked rotor torque : 250 % Breakdown torque : 300 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 0.1279 sq.ft.lb Design : B 50% 100% Output 75% Foundation loads 85.5 : 57 lb Efficiency (%) 82.5 85.5 Max. traction Power Factor 0.73 0.83 0.89 Max. compression : 98 lb Losses at normative operating points (speed;torque), in percentage of rated output power P2 (0,5;1,0) P3 (0,25;1,0) P4 (0,9;0,5) P6 (0,5;0,25) P1 (0,9;1,0) P5 (0,5;0,5) P7 (0,25;0,25) 15.4 10.7 9.4 9.5 4.8 3.5 1.9 Drive end Non drive end Bearing type 6205 ZZ 6203 ZZ V'Ring Sealing Without Bearing Seal Lubrication interval Lubricant amount Lubricant type Mobil Polyrex EM Notes: This revision replaces and cancel the previous one, which These are average values based on tests with sinusoidal must be eliminated. power supply, subject to the tolerances stipulated in NEMA (1) Looking the motor from the shaft end. MG-1. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load. Rev. **Changes Summary** Performed Checked Date Performed by Checked by Page Revision

1/1

27/03/2024

Date