DATA SHEET

Three Phase Induction Motor - Squirrel Cage



				-		
Customer	:					
Product line		ed Steel l e-Phase	NEMA Prem	iium Efficier	ncy Product code : Catalog # :	12617113 00112OT3E145T-S
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia Design	9	: 6 : 60 F : 230/ : 3.30 : 20.1 : 6.1x : 2.26 : 1150 : 4.17 : 4.57 : 250 : 300 : F : 1.15	P (0.75 kW) dz 460 V /1.65 A /10.1 A (Code K) /1.13 A) rpm 9% ft.lb %		Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 43s (cold) 24s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IC01 - ODP : F-1 : Both (CW and CCW) : 50.0 dB(A) : Direct On Line : 34.9 lb
Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	76.5	76.6	.8 81.5 79.5 79.1	78.6	Max. traction	: 114 lb
Power Factor	0.26 0.31 0.26	0.47 0.5 0.48	0.60 0.69 0.62	0.69 0.77 0.72	Max. compression	: 149 lb
Bearing type Sealing Lubrication interva Lubricant amount Lubricant type		: : : :	Drive 6208 Without Be	5 ZZ earing Seal	Non drive end 6203 ZZ Without Bearing Se - - bil Polyrex EM	al

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

, ,					
Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	26/03/2024	1		1/1	