

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Premium Efficiency Three-Phase

Product code : 12808935

Catalog # : .2518OT3E56CFL-S

Frame : 56C
 Output : 0.25 HP (0.18 kW)
 Poles : 4
 Frequency : 60 Hz
 Rated voltage : 208-230/460 V
 Rated current : 1.18-1.07/0.533 A
 L. R. Amperes : 6.96-6.29/3.14 A
 LRC : 5.9x(Code M)
 No load current : 0.862-1.00/0.500 A
 Rated speed : 1765 rpm
 Slip : 1.94 %
 Rated torque : 0.744 ft.lb
 Locked rotor torque : 229 %
 Breakdown torque : 330 %
 Insulation class : F
 Service factor : 1.35
 Moment of inertia (J) : 0.0389 sq.ft.lb

Locked rotor time : 68s (cold) 38s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : -20°C to +40°C
 Altitude : 1000 m.a.s.l.
 Cooling method : IC01 - ODP
 Mounting : F-1
 Rotation¹ : Both (CW and CCW)
 Noise level² : 52.0 dB(A)
 Starting method : Direct On Line
 Approx. weight³ : 16.2 lb

Output	25%		50%		75%		100%	
Efficiency (%)	53.6	56.6	57.5	59.2	64.0	66.3	69.5	69.4
	50.7		54.0		62.5		67.1	
Power Factor	0.22	0.27	0.41	0.48	0.52	0.59	0.61	0.69
	0.23		0.42		0.52		0.61	

Foundation loads
 Max. traction : 21 lb
 Max. compression : 37 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6203 ZZ	6202 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
			Revision	