

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium Efficiency  
Three-Phase

Product code : 12675367

Catalog # : 00718ET3E213TC-S

Frame : 213/5TC  
Output : 7.5 HP (5.5 kW)  
Poles : 4  
Frequency : 60 Hz  
Rated voltage : 230/460 V  
Rated current : 18.4/9.18 A  
L. R. Amperes : 134/67.0 A  
LRC : 7.3x(Code J)  
No load current : 8.81/4.41 A  
Rated speed : 1770 rpm  
Slip : 1.67 %  
Rated torque : 22.3 ft.lb  
Locked rotor torque : 260 %  
Breakdown torque : 300 %  
Insulation class : F  
Service factor : 1.15  
Moment of inertia (J) : 0.9380 sq.ft.lb  
Design : B

Locked rotor time : 32s (cold) 18s (hot)  
Temperature rise : 80 K  
Duty cycle : Cont.(S1)  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Protection degree : IP55  
Cooling method : IC411 - TEFC  
Mounting : F-1  
Rotation<sup>1</sup> : Both (CW and CCW)  
Noise level<sup>2</sup> : 60.0 dB(A)  
Starting method : Direct On Line  
Approx. weight<sup>3</sup> : 127 lb

Output	50%	75%	100%
Efficiency (%)	90.2 90.2 89.4	91.0 90.0 90.1	91.7 88.6 89.4
Power Factor	0.64 0.71 0.64	0.76 0.82 0.76	0.82 0.86 0.83

Foundation loads  
Max. traction : 391 lb  
Max. compression : 519 lb

	Drive end	Non drive end
Bearing type	6208 ZZ	6206 ZZ
Sealing	V'Ring	Without Bearing Seal
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
		Revision		