

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																																																																																									
Product line		Rolled Steel Premium Efficiency Three-Phase	Product code :	12808928																																																																																					
			Catalog # :	.2512OT3E56C-S																																																																																					
<table> <tr><td>Frame</td><td>:</td><td>56C</td><td>Locked rotor time</td><td>: 72s (cold) 40s (hot)</td></tr> <tr><td>Output</td><td>:</td><td>0.25 HP (0.18 kW)</td><td>Temperature rise</td><td>: 80 K</td></tr> <tr><td>Poles</td><td>:</td><td>6</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>:</td><td>60 Hz</td><td>Ambient temperature</td><td>: -20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>:</td><td>208-230/460 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>:</td><td>1.21-1.10/0.549 A</td><td>Cooling method</td><td>: IC01 - ODP</td></tr> <tr><td>L. R. Amperes</td><td>:</td><td>5.83-5.27/2.64 A</td><td>Mounting</td><td>: F-1</td></tr> <tr><td>LRC</td><td>:</td><td>4.8x(Code K)</td><td>Rotation¹</td><td>: Both (CW and CCW)</td></tr> <tr><td>No load current</td><td>:</td><td>0.862-1.00/0.500 A</td><td>Noise level²</td><td>: 50.0 dB(A)</td></tr> <tr><td>Rated speed</td><td>:</td><td>1160 rpm</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Slip</td><td>:</td><td>3.33 %</td><td>Approx. weight³</td><td>: 17.1 lb</td></tr> <tr><td>Rated torque</td><td>:</td><td>1.13 ft.lb</td><td></td><td></td></tr> <tr><td>Locked rotor torque</td><td>:</td><td>210 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>:</td><td>280 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>:</td><td>F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>:</td><td>1.35</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>:</td><td>0.0622 sq.ft.lb</td><td></td><td></td></tr> </table>				Frame	:	56C	Locked rotor time	: 72s (cold) 40s (hot)	Output	:	0.25 HP (0.18 kW)	Temperature rise	: 80 K	Poles	:	6	Duty cycle	: Cont.(S1)	Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C	Rated voltage	:	208-230/460 V	Altitude	: 1000 m.a.s.l.	Rated current	:	1.21-1.10/0.549 A	Cooling method	: IC01 - ODP	L. R. Amperes	:	5.83-5.27/2.64 A	Mounting	: F-1	LRC	:	4.8x(Code K)	Rotation ¹	: Both (CW and CCW)	No load current	:	0.862-1.00/0.500 A	Noise level ²	: 50.0 dB(A)	Rated speed	:	1160 rpm	Starting method	: Direct On Line	Slip	:	3.33 %	Approx. weight ³	: 17.1 lb	Rated torque	:	1.13 ft.lb			Locked rotor torque	:	210 %			Breakdown torque	:	280 %			Insulation class	:	F			Service factor	:	1.35			Moment of inertia (J)	:	0.0622 sq.ft.lb			
Frame	:	56C	Locked rotor time	: 72s (cold) 40s (hot)																																																																																					
Output	:	0.25 HP (0.18 kW)	Temperature rise	: 80 K																																																																																					
Poles	:	6	Duty cycle	: Cont.(S1)																																																																																					
Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C																																																																																					
Rated voltage	:	208-230/460 V	Altitude	: 1000 m.a.s.l.																																																																																					
Rated current	:	1.21-1.10/0.549 A	Cooling method	: IC01 - ODP																																																																																					
L. R. Amperes	:	5.83-5.27/2.64 A	Mounting	: F-1																																																																																					
LRC	:	4.8x(Code K)	Rotation ¹	: Both (CW and CCW)																																																																																					
No load current	:	0.862-1.00/0.500 A	Noise level ²	: 50.0 dB(A)																																																																																					
Rated speed	:	1160 rpm	Starting method	: Direct On Line																																																																																					
Slip	:	3.33 %	Approx. weight ³	: 17.1 lb																																																																																					
Rated torque	:	1.13 ft.lb																																																																																							
Locked rotor torque	:	210 %																																																																																							
Breakdown torque	:	280 %																																																																																							
Insulation class	:	F																																																																																							
Service factor	:	1.35																																																																																							
Moment of inertia (J)	:	0.0622 sq.ft.lb																																																																																							
Output	25%	50%	75%	100%	Foundation loads																																																																																				
Efficiency (%)	52.2	55.9	55.0	57.9	64.0	64.3	67.5	66.4	Max. traction	: 27 lb																																																																															
	50.3		53.2		61.3		65.1		Max. compression	: 44 lb																																																																															
Power Factor	0.22	0.27	0.41	0.48	0.52	0.60	0.61	0.70																																																																																	
	0.24		0.43		0.54		0.63																																																																																		
<table> <tr><td colspan="2">Bearing type</td><td>Drive end</td><td>Non drive end</td><td></td></tr> <tr><td colspan="2">:</td><td>6203 ZZ</td><td>6202 ZZ</td><td></td></tr> <tr><td colspan="2">Sealing</td><td>Without Bearing Seal</td><td>Without Bearing Seal</td><td></td></tr> <tr><td colspan="2">Lubrication interval</td><td>-</td><td>-</td><td></td></tr> <tr><td colspan="2">Lubricant amount</td><td>-</td><td>-</td><td></td></tr> <tr><td colspan="2">Lubricant type</td><td>Mobil Polyrex EM</td><td></td><td></td></tr> </table>					Bearing type		Drive end	Non drive end		:		6203 ZZ	6202 ZZ		Sealing		Without Bearing Seal	Without Bearing Seal		Lubrication interval		-	-		Lubricant amount		-	-		Lubricant type		Mobil Polyrex EM																																																									
Bearing type		Drive end	Non drive end																																																																																						
:		6203 ZZ	6202 ZZ																																																																																						
Sealing		Without Bearing Seal	Without Bearing Seal																																																																																						
Lubrication interval		-	-																																																																																						
Lubricant amount		-	-																																																																																						
Lubricant type		Mobil Polyrex EM																																																																																							
Notes:																																																																																									
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>					These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																																																																				
Rev.	Changes Summary				Performed	Checked	Date																																																																																		
Performed by					Page		Revision																																																																																		
Checked by																																																																																									
Date	27/03/2024																																																																																								
Customer :																																																																																									
Product line		Rolled Steel Premium Efficiency Three-Phase	Product code :	12808928																																																																																					
			Catalog # :	.2512OT3E56C-S																																																																																					
<table> <tr><td>Frame</td><td>:</td><td>56C</td><td>Locked rotor time</td><td>: 72s (cold) 40s (hot)</td></tr> <tr><td>Output</td><td>:</td><td>0.25 HP (0.18 kW)</td><td>Temperature rise</td><td>: 80 K</td></tr> <tr><td>Poles</td><td>:</td><td>6</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>:</td><td>60 Hz</td><td>Ambient temperature</td><td>: -20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>:</td><td>208-230/460 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>:</td><td>1.21-1.10/0.549 A</td><td>Cooling method</td><td>: IC01 - ODP</td></tr> <tr><td>L. R. Amperes</td><td>:</td><td>5.83-5.27/2.64 A</td><td>Mounting</td><td>: F-1</td></tr> <tr><td>LRC</td><td>:</td><td>4.8x(Code K)</td><td>Rotation¹</td><td>: Both (CW and CCW)</td></tr> <tr><td>No load current</td><td>:</td><td>0.862-1.00/0.500 A</td><td>Noise level²</td><td>: 50.0 dB(A)</td></tr> <tr><td>Rated speed</td><td>:</td><td>1160 rpm</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Slip</td><td>:</td><td>3.33 %</td><td>Approx. weight³</td><td>: 17.1 lb</td></tr> <tr><td>Rated torque</td><td>:</td><td>1.13 ft.lb</td><td></td><td></td></tr> <tr><td>Locked rotor torque</td><td>:</td><td>210 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>:</td><td>280 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>:</td><td>F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>:</td><td>1.35</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>:</td><td>0.0622 sq.ft.lb</td><td></td><td></td></tr> </table>				Frame	:	56C	Locked rotor time	: 72s (cold) 40s (hot)	Output	:	0.25 HP (0.18 kW)	Temperature rise	: 80 K	Poles	:	6	Duty cycle	: Cont.(S1)	Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C	Rated voltage	:	208-230/460 V	Altitude	: 1000 m.a.s.l.	Rated current	:	1.21-1.10/0.549 A	Cooling method	: IC01 - ODP	L. R. Amperes	:	5.83-5.27/2.64 A	Mounting	: F-1	LRC	:	4.8x(Code K)	Rotation ¹	: Both (CW and CCW)	No load current	:	0.862-1.00/0.500 A	Noise level ²	: 50.0 dB(A)	Rated speed	:	1160 rpm	Starting method	: Direct On Line	Slip	:	3.33 %	Approx. weight ³	: 17.1 lb	Rated torque	:	1.13 ft.lb			Locked rotor torque	:	210 %			Breakdown torque	:	280 %			Insulation class	:	F			Service factor	:	1.35			Moment of inertia (J)	:	0.0622 sq.ft.lb			
Frame	:	56C	Locked rotor time	: 72s (cold) 40s (hot)																																																																																					
Output	:	0.25 HP (0.18 kW)	Temperature rise	: 80 K																																																																																					
Poles	:	6	Duty cycle	: Cont.(S1)																																																																																					
Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C																																																																																					
Rated voltage	:	208-230/460 V	Altitude	: 1000 m.a.s.l.																																																																																					
Rated current	:	1.21-1.10/0.549 A	Cooling method	: IC01 - ODP																																																																																					
L. R. Amperes	:	5.83-5.27/2.64 A	Mounting	: F-1																																																																																					
LRC	:	4.8x(Code K)	Rotation ¹	: Both (CW and CCW)																																																																																					
No load current	:	0.862-1.00/0.500 A	Noise level ²	: 50.0 dB(A)																																																																																					
Rated speed	:	1160 rpm	Starting method	: Direct On Line																																																																																					
Slip	:	3.33 %	Approx. weight ³	: 17.1 lb																																																																																					
Rated torque	:	1.13 ft.lb																																																																																							
Locked rotor torque	:	210 %																																																																																							
Breakdown torque	:	280 %																																																																																							
Insulation class	:	F																																																																																							
Service factor	:	1.35																																																																																							
Moment of inertia (J)	:	0.0622 sq.ft.lb																																																																																							
Output	25%	50%	75%	100%	Foundation loads																																																																																				
Efficiency (%)	52.2	55.9	55.0	57.9	64.0	64.3	67.5	66.4	Max. traction	: 27 lb																																																																															
	50.3		53.2		61.3		65.1		Max. compression	: 44 lb																																																																															
Power Factor	0.22	0.27	0.41	0.48	0.52	0.60	0.61	0.70																																																																																	
	0.24		0.43		0.54		0.63																																																																																		
<table> <tr><td colspan="2">Bearing type</td><td>Drive end</td><td>Non drive end</td><td></td></tr> <tr><td colspan="2">:</td><td>6203 ZZ</td><td>6202 ZZ</td><td></td></tr> <tr><td colspan="2">Sealing</td><td>Without Bearing Seal</td><td>Without Bearing Seal</td><td></td></tr> <tr><td colspan="2">Lubrication interval</td><td>-</td><td>-</td><td></td></tr> <tr><td colspan="2">Lubricant amount</td><td>-</td><td>-</td><td></td></tr> <tr><td colspan="2">Lubricant type</td><td>Mobil Polyrex EM</td><td></td><td></td></tr> </table>					Bearing type		Drive end	Non drive end		:		6203 ZZ	6202 ZZ		Sealing		Without Bearing Seal	Without Bearing Seal		Lubrication interval		-	-		Lubricant amount		-	-		Lubricant type		Mobil Polyrex EM																																																									
Bearing type		Drive end	Non drive end																																																																																						
:		6203 ZZ	6202 ZZ																																																																																						
Sealing		Without Bearing Seal	Without Bearing Seal																																																																																						
Lubrication interval		-	-																																																																																						
Lubricant amount		-	-																																																																																						
Lubricant type		Mobil Polyrex EM																																																																																							
Notes:																																																																																									
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>					These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																																																																				
Rev.	Changes Summary				Performed	Checked	Date																																																																																		
Performed by					Page		Revision																																																																																		
Checked by																																																																																									
Date	27/03/2024																																																																																								