

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																																																																							
Product line	: Rolled Steel Premium Efficiency Three-Phase		Product code :	12809009																																																																			
			Catalog # :	.3312OT3E56-S																																																																			
<table> <tr><td>Frame</td><td>: 56</td><td>Locked rotor time</td><td>: 63s (cold) 35s (hot)</td></tr> <tr><td>Output</td><td>: 0.33 HP (0.25 kW)</td><td>Temperature rise</td><td>: 80 K</td></tr> <tr><td>Poles</td><td>: 6</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>: 60 Hz</td><td>Ambient temperature</td><td>: -20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>: 208-230/460 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>: 1.54-1.40/0.698 A</td><td>Cooling method</td><td>: IC01 - ODP</td></tr> <tr><td>L. R. Amperes</td><td>: 7.72-6.98/3.49 A</td><td>Mounting</td><td>: F-1</td></tr> <tr><td>LRC</td><td>: 5.0x(Code K)</td><td>Rotation¹</td><td>: Both (CW and CCW)</td></tr> <tr><td>No load current</td><td>: 1.03-1.20/0.600 A</td><td>Noise level²</td><td>: 50.0 dB(A)</td></tr> <tr><td>Rated speed</td><td>: 1160 rpm</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Slip</td><td>: 3.33 %</td><td>Approx. weight³</td><td>: 18.5 lb</td></tr> <tr><td>Rated torque</td><td>: 1.49 ft.lb</td><td></td><td></td></tr> <tr><td>Locked rotor torque</td><td>: 210 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>: 280 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>: F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>: 1.35</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>: 0.0710 sq.ft.lb</td><td></td><td></td></tr> </table>				Frame	: 56	Locked rotor time	: 63s (cold) 35s (hot)	Output	: 0.33 HP (0.25 kW)	Temperature rise	: 80 K	Poles	: 6	Duty cycle	: Cont.(S1)	Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C	Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.	Rated current	: 1.54-1.40/0.698 A	Cooling method	: IC01 - ODP	L. R. Amperes	: 7.72-6.98/3.49 A	Mounting	: F-1	LRC	: 5.0x(Code K)	Rotation ¹	: Both (CW and CCW)	No load current	: 1.03-1.20/0.600 A	Noise level ²	: 50.0 dB(A)	Rated speed	: 1160 rpm	Starting method	: Direct On Line	Slip	: 3.33 %	Approx. weight ³	: 18.5 lb	Rated torque	: 1.49 ft.lb			Locked rotor torque	: 210 %			Breakdown torque	: 280 %			Insulation class	: F			Service factor	: 1.35			Moment of inertia (J)	: 0.0710 sq.ft.lb		
Frame	: 56	Locked rotor time	: 63s (cold) 35s (hot)																																																																				
Output	: 0.33 HP (0.25 kW)	Temperature rise	: 80 K																																																																				
Poles	: 6	Duty cycle	: Cont.(S1)																																																																				
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C																																																																				
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.																																																																				
Rated current	: 1.54-1.40/0.698 A	Cooling method	: IC01 - ODP																																																																				
L. R. Amperes	: 7.72-6.98/3.49 A	Mounting	: F-1																																																																				
LRC	: 5.0x(Code K)	Rotation ¹	: Both (CW and CCW)																																																																				
No load current	: 1.03-1.20/0.600 A	Noise level ²	: 50.0 dB(A)																																																																				
Rated speed	: 1160 rpm	Starting method	: Direct On Line																																																																				
Slip	: 3.33 %	Approx. weight ³	: 18.5 lb																																																																				
Rated torque	: 1.49 ft.lb																																																																						
Locked rotor torque	: 210 %																																																																						
Breakdown torque	: 280 %																																																																						
Insulation class	: F																																																																						
Service factor	: 1.35																																																																						
Moment of inertia (J)	: 0.0710 sq.ft.lb																																																																						
Output	25%	50%	75%	100%																																																																			
Efficiency (%)	55.6	61.4	59.5	62.7	66.0	67.9	71.4	68.8																																																															
	55.7	58.1	65.3	68.1																																																																			
Power Factor	0.23	0.27	0.42	0.50	0.53	0.63	0.63	0.73																																																															
	0.24	0.44	0.56	0.66																																																																			
<table> <tr> <td colspan="2"></td><td>Drive end</td><td colspan="2">Non drive end</td></tr> <tr> <td>Bearing type</td><td>: 6203 ZZ</td><td>6202 ZZ</td><td colspan="2"></td></tr> <tr> <td>Sealing</td><td>: Without Bearing Seal</td><td>Without Bearing Seal</td><td colspan="2"></td></tr> <tr> <td>Lubrication interval</td><td>: -</td><td>-</td><td colspan="2"></td></tr> <tr> <td>Lubricant amount</td><td>: -</td><td>-</td><td colspan="2"></td></tr> <tr> <td>Lubricant type</td><td>: Mobil Polyrex EM</td><td></td><td colspan="2" rowspan="4"></td></tr> </table>							Drive end	Non drive end		Bearing type	: 6203 ZZ	6202 ZZ			Sealing	: Without Bearing Seal	Without Bearing Seal			Lubrication interval	: -	-			Lubricant amount	: -	-			Lubricant type	: Mobil Polyrex EM																																								
		Drive end	Non drive end																																																																				
Bearing type	: 6203 ZZ	6202 ZZ																																																																					
Sealing	: Without Bearing Seal	Without Bearing Seal																																																																					
Lubrication interval	: -	-																																																																					
Lubricant amount	: -	-																																																																					
Lubricant type	: Mobil Polyrex EM																																																																						
Notes:																																																																							
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>																																																																							
These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																																																							
Rev.	Changes Summary			Performed	Checked	Date																																																																	
Performed by					Page	Revision																																																																	
Checked by																																																																							
Date	27/03/2024				1 / 1																																																																		
Customer :																																																																							
Product line	: Rolled Steel Premium Efficiency Three-Phase		Product code :	12809009																																																																			
			Catalog # :	.3312OT3E56-S																																																																			
<table> <tr><td>Frame</td><td>: 56</td><td>Locked rotor time</td><td>: 63s (cold) 35s (hot)</td></tr> <tr><td>Output</td><td>: 0.33 HP (0.25 kW)</td><td>Temperature rise</td><td>: 80 K</td></tr> <tr><td>Poles</td><td>: 6</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>: 60 Hz</td><td>Ambient temperature</td><td>: -20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>: 208-230/460 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>: 1.54-1.40/0.698 A</td><td>Cooling method</td><td>: IC01 - ODP</td></tr> <tr><td>L. R. Amperes</td><td>: 7.72-6.98/3.49 A</td><td>Mounting</td><td>: F-1</td></tr> <tr><td>LRC</td><td>: 5.0x(Code K)</td><td>Rotation¹</td><td>: Both (CW and CCW)</td></tr> <tr><td>No load current</td><td>: 1.03-1.20/0.600 A</td><td>Noise level²</td><td>: 50.0 dB(A)</td></tr> <tr><td>Rated speed</td><td>: 1160 rpm</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Slip</td><td>: 3.33 %</td><td>Approx. weight³</td><td>: 18.5 lb</td></tr> <tr><td>Rated torque</td><td>: 1.49 ft.lb</td><td></td><td></td></tr> <tr><td>Locked rotor torque</td><td>: 210 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>: 280 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>: F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>: 1.35</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>: 0.0710 sq.ft.lb</td><td></td><td></td></tr> </table>				Frame	: 56	Locked rotor time	: 63s (cold) 35s (hot)	Output	: 0.33 HP (0.25 kW)	Temperature rise	: 80 K	Poles	: 6	Duty cycle	: Cont.(S1)	Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C	Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.	Rated current	: 1.54-1.40/0.698 A	Cooling method	: IC01 - ODP	L. R. Amperes	: 7.72-6.98/3.49 A	Mounting	: F-1	LRC	: 5.0x(Code K)	Rotation ¹	: Both (CW and CCW)	No load current	: 1.03-1.20/0.600 A	Noise level ²	: 50.0 dB(A)	Rated speed	: 1160 rpm	Starting method	: Direct On Line	Slip	: 3.33 %	Approx. weight ³	: 18.5 lb	Rated torque	: 1.49 ft.lb			Locked rotor torque	: 210 %			Breakdown torque	: 280 %			Insulation class	: F			Service factor	: 1.35			Moment of inertia (J)	: 0.0710 sq.ft.lb		
Frame	: 56	Locked rotor time	: 63s (cold) 35s (hot)																																																																				
Output	: 0.33 HP (0.25 kW)	Temperature rise	: 80 K																																																																				
Poles	: 6	Duty cycle	: Cont.(S1)																																																																				
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C																																																																				
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.																																																																				
Rated current	: 1.54-1.40/0.698 A	Cooling method	: IC01 - ODP																																																																				
L. R. Amperes	: 7.72-6.98/3.49 A	Mounting	: F-1																																																																				
LRC	: 5.0x(Code K)	Rotation ¹	: Both (CW and CCW)																																																																				
No load current	: 1.03-1.20/0.600 A	Noise level ²	: 50.0 dB(A)																																																																				
Rated speed	: 1160 rpm	Starting method	: Direct On Line																																																																				
Slip	: 3.33 %	Approx. weight ³	: 18.5 lb																																																																				
Rated torque	: 1.49 ft.lb																																																																						
Locked rotor torque	: 210 %																																																																						
Breakdown torque	: 280 %																																																																						
Insulation class	: F																																																																						
Service factor	: 1.35																																																																						
Moment of inertia (J)	: 0.0710 sq.ft.lb																																																																						
Output	25%	50%	75%	100%	Foundation loads																																																																		
Efficiency (%)	55.6	61.4	59.5	62.7	Max. traction	: 37 lb																																																																	
	55.7	58.1	65.3	68.1	Max. compression	: 55 lb																																																																	
Power Factor	0.23	0.27	0.42	0.50																																																																			
	0.24	0.44	0.56	0.66																																																																			
<table> <tr> <td colspan="2"></td><td>Drive end</td><td colspan="2">Non drive end</td></tr> <tr> <td>Bearing type</td><td>: 6203 ZZ</td><td>6202 ZZ</td><td colspan="2"></td></tr> <tr> <td>Sealing</td><td>: Without Bearing Seal</td><td>Without Bearing Seal</td><td colspan="2"></td></tr> <tr> <td>Lubrication interval</td><td>: -</td><td>-</td><td colspan="2"></td></tr> <tr> <td>Lubricant amount</td><td>: -</td><td>-</td><td colspan="2"></td></tr> <tr> <td>Lubricant type</td><td>: Mobil Polyrex EM</td><td></td><td colspan="2" rowspan="4"></td></tr> </table>							Drive end	Non drive end		Bearing type	: 6203 ZZ	6202 ZZ			Sealing	: Without Bearing Seal	Without Bearing Seal			Lubrication interval	: -	-			Lubricant amount	: -	-			Lubricant type	: Mobil Polyrex EM																																								
		Drive end	Non drive end																																																																				
Bearing type	: 6203 ZZ	6202 ZZ																																																																					
Sealing	: Without Bearing Seal	Without Bearing Seal																																																																					
Lubrication interval	: -	-																																																																					
Lubricant amount	: -	-																																																																					
Lubricant type	: Mobil Polyrex EM																																																																						
Notes:																																																																							
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>																																																																							
These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																																																							
Rev.	Changes Summary			Performed	Checked	Date																																																																	
Performed by					Page	Revision																																																																	
Checked by																																																																							
Date	27/03/2024				1 / 1																																																																		