

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																																																																																																
Product line		: Rolled Steel Premium Efficiency Three-Phase		Product code : 12809205																																																																																												
				Catalog # : .5018OT3E56C-S																																																																																												
<table> <tr><td>Frame</td><td>:</td><td>56C</td><td>Locked rotor time</td><td>: 48s (cold) 27s (hot)</td></tr> <tr><td>Output</td><td>:</td><td>0.5 HP (0.37 kW)</td><td>Temperature rise</td><td>: 80 K</td></tr> <tr><td>Poles</td><td>:</td><td>4</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>:</td><td>60 Hz</td><td>Ambient temperature</td><td>: -20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>:</td><td>208-230/460 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>:</td><td>1.90-1.72/0.861 A</td><td>Cooling method</td><td>: IC01 - ODP</td></tr> <tr><td>L. R. Amperes</td><td>:</td><td>13.7-12.4/6.20 A</td><td>Mounting</td><td>: F-1</td></tr> <tr><td>LRC</td><td>:</td><td>7.2x(Code L)</td><td>Rotation¹</td><td>: Both (CW and CCW)</td></tr> <tr><td>No load current</td><td>:</td><td>1.12-1.30/0.650 A</td><td>Noise level²</td><td>: 52.0 dB(A)</td></tr> <tr><td>Rated speed</td><td>:</td><td>1765 rpm</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Slip</td><td>:</td><td>1.94 %</td><td>Approx. weight³</td><td>: 20.9 lb</td></tr> <tr><td>Rated torque</td><td>:</td><td>1.49 ft.lb</td><td></td><td></td></tr> <tr><td>Locked rotor torque</td><td>:</td><td>240 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>:</td><td>330 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>:</td><td>F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>:</td><td>1.25</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>:</td><td>0.0584 sq.ft.lb</td><td></td><td></td></tr> </table>				Frame	:	56C	Locked rotor time	: 48s (cold) 27s (hot)	Output	:	0.5 HP (0.37 kW)	Temperature rise	: 80 K	Poles	:	4	Duty cycle	: Cont.(S1)	Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C	Rated voltage	:	208-230/460 V	Altitude	: 1000 m.a.s.l.	Rated current	:	1.90-1.72/0.861 A	Cooling method	: IC01 - ODP	L. R. Amperes	:	13.7-12.4/6.20 A	Mounting	: F-1	LRC	:	7.2x(Code L)	Rotation ¹	: Both (CW and CCW)	No load current	:	1.12-1.30/0.650 A	Noise level ²	: 52.0 dB(A)	Rated speed	:	1765 rpm	Starting method	: Direct On Line	Slip	:	1.94 %	Approx. weight ³	: 20.9 lb	Rated torque	:	1.49 ft.lb			Locked rotor torque	:	240 %			Breakdown torque	:	330 %			Insulation class	:	F			Service factor	:	1.25			Moment of inertia (J)	:	0.0584 sq.ft.lb										
Frame	:	56C	Locked rotor time	: 48s (cold) 27s (hot)																																																																																												
Output	:	0.5 HP (0.37 kW)	Temperature rise	: 80 K																																																																																												
Poles	:	4	Duty cycle	: Cont.(S1)																																																																																												
Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C																																																																																												
Rated voltage	:	208-230/460 V	Altitude	: 1000 m.a.s.l.																																																																																												
Rated current	:	1.90-1.72/0.861 A	Cooling method	: IC01 - ODP																																																																																												
L. R. Amperes	:	13.7-12.4/6.20 A	Mounting	: F-1																																																																																												
LRC	:	7.2x(Code L)	Rotation ¹	: Both (CW and CCW)																																																																																												
No load current	:	1.12-1.30/0.650 A	Noise level ²	: 52.0 dB(A)																																																																																												
Rated speed	:	1765 rpm	Starting method	: Direct On Line																																																																																												
Slip	:	1.94 %	Approx. weight ³	: 20.9 lb																																																																																												
Rated torque	:	1.49 ft.lb																																																																																														
Locked rotor torque	:	240 %																																																																																														
Breakdown torque	:	330 %																																																																																														
Insulation class	:	F																																																																																														
Service factor	:	1.25																																																																																														
Moment of inertia (J)	:	0.0584 sq.ft.lb																																																																																														
Output	25%	50%	75%	100%	Foundation loads																																																																																											
Efficiency (%)	67.5	71.5	70.0	72.6	75.5	76.6	78.2	77.4	Max. traction : 46 lb																																																																																							
	66.8		68.9		74.6		76.7		Max. compression : 67 lb																																																																																							
Power Factor	0.26	0.31	0.47	0.55	0.60	0.68	0.69	0.77																																																																																								
0.26		0.47		0.60		0.70																																																																																										
<table> <tr><td>Bearing type</td><td>:</td><td>6203 ZZ</td><td>Drive end</td><td>Non drive end</td></tr> <tr><td>Sealing</td><td>:</td><td>Without Bearing Seal</td><td>6202 ZZ</td><td>Without Bearing Seal</td></tr> <tr><td>Lubrication interval</td><td>:</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>Lubricant amount</td><td>:</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>Lubricant type</td><td>:</td><td colspan="3" rowspan="5">Mobil Polyrex EM</td></tr> </table>					Bearing type	:	6203 ZZ	Drive end	Non drive end	Sealing	:	Without Bearing Seal	6202 ZZ	Without Bearing Seal	Lubrication interval	:	-	-	-	Lubricant amount	:	-	-	-	Lubricant type	:	Mobil Polyrex EM																																																																					
Bearing type	:	6203 ZZ	Drive end	Non drive end																																																																																												
Sealing	:	Without Bearing Seal	6202 ZZ	Without Bearing Seal																																																																																												
Lubrication interval	:	-	-	-																																																																																												
Lubricant amount	:	-	-	-																																																																																												
Lubricant type	:	Mobil Polyrex EM																																																																																														
Notes:																																																																																																
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>					These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																																																																											
Rev.	Changes Summary				Performed	Checked	Date																																																																																									
Performed by						Page		Revision																																																																																								
Checked by																																																																																																
Date	27/03/2024																																																																																															
Customer :																																																																																																
Product line		: Rolled Steel Premium Efficiency Three-Phase		Product code : 12809205																																																																																												
				Catalog # : .5018OT3E56C-S																																																																																												
<table> <tr><td>Frame</td><td>:</td><td>56C</td><td>Locked rotor time</td><td>: 48s (cold) 27s (hot)</td></tr> <tr><td>Output</td><td>:</td><td>0.5 HP (0.37 kW)</td><td>Temperature rise</td><td>: 80 K</td></tr> <tr><td>Poles</td><td>:</td><td>4</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>:</td><td>60 Hz</td><td>Ambient temperature</td><td>: -20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>:</td><td>208-230/460 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>:</td><td>1.90-1.72/0.861 A</td><td>Cooling method</td><td>: IC01 - ODP</td></tr> <tr><td>L. R. Amperes</td><td>:</td><td>13.7-12.4/6.20 A</td><td>Mounting</td><td>: F-1</td></tr> <tr><td>LRC</td><td>:</td><td>7.2x(Code L)</td><td>Rotation¹</td><td>: Both (CW and CCW)</td></tr> <tr><td>No load current</td><td>:</td><td>1.12-1.30/0.650 A</td><td>Noise level²</td><td>: 52.0 dB(A)</td></tr> <tr><td>Rated speed</td><td>:</td><td>1765 rpm</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Slip</td><td>:</td><td>1.94 %</td><td>Approx. weight³</td><td>: 20.9 lb</td></tr> <tr><td>Rated torque</td><td>:</td><td>1.49 ft.lb</td><td></td><td></td></tr> <tr><td>Locked rotor torque</td><td>:</td><td>240 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>:</td><td>330 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>:</td><td>F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>:</td><td>1.25</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>:</td><td>0.0584 sq.ft.lb</td><td></td><td></td></tr> </table>				Frame	:	56C	Locked rotor time	: 48s (cold) 27s (hot)	Output	:	0.5 HP (0.37 kW)	Temperature rise	: 80 K	Poles	:	4	Duty cycle	: Cont.(S1)	Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C	Rated voltage	:	208-230/460 V	Altitude	: 1000 m.a.s.l.	Rated current	:	1.90-1.72/0.861 A	Cooling method	: IC01 - ODP	L. R. Amperes	:	13.7-12.4/6.20 A	Mounting	: F-1	LRC	:	7.2x(Code L)	Rotation ¹	: Both (CW and CCW)	No load current	:	1.12-1.30/0.650 A	Noise level ²	: 52.0 dB(A)	Rated speed	:	1765 rpm	Starting method	: Direct On Line	Slip	:	1.94 %	Approx. weight ³	: 20.9 lb	Rated torque	:	1.49 ft.lb			Locked rotor torque	:	240 %			Breakdown torque	:	330 %			Insulation class	:	F			Service factor	:	1.25			Moment of inertia (J)	:	0.0584 sq.ft.lb										
Frame	:	56C	Locked rotor time	: 48s (cold) 27s (hot)																																																																																												
Output	:	0.5 HP (0.37 kW)	Temperature rise	: 80 K																																																																																												
Poles	:	4	Duty cycle	: Cont.(S1)																																																																																												
Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C																																																																																												
Rated voltage	:	208-230/460 V	Altitude	: 1000 m.a.s.l.																																																																																												
Rated current	:	1.90-1.72/0.861 A	Cooling method	: IC01 - ODP																																																																																												
L. R. Amperes	:	13.7-12.4/6.20 A	Mounting	: F-1																																																																																												
LRC	:	7.2x(Code L)	Rotation ¹	: Both (CW and CCW)																																																																																												
No load current	:	1.12-1.30/0.650 A	Noise level ²	: 52.0 dB(A)																																																																																												
Rated speed	:	1765 rpm	Starting method	: Direct On Line																																																																																												
Slip	:	1.94 %	Approx. weight ³	: 20.9 lb																																																																																												
Rated torque	:	1.49 ft.lb																																																																																														
Locked rotor torque	:	240 %																																																																																														
Breakdown torque	:	330 %																																																																																														
Insulation class	:	F																																																																																														
Service factor	:	1.25																																																																																														
Moment of inertia (J)	:	0.0584 sq.ft.lb																																																																																														
Output	25%	50%	75%	100%	Foundation loads																																																																																											
Efficiency (%)	67.5	71.5	70.0	72.6	75.5	76.6	78.2	77.4	Max. traction : 46 lb																																																																																							
	66.8		68.9		74.6		76.7		Max. compression : 67 lb																																																																																							
Power Factor	0.26	0.31	0.47	0.55	0.60	0.68	0.69	0.77																																																																																								
	0.26		0.47		0.60		0.70																																																																																									
<table> <tr><td>Bearing type</td><td>:</td><td>6203 ZZ</td><td>Drive end</td><td>Non drive end</td></tr> <tr><td>Sealing</td><td>:</td><td>Without Bearing Seal</td><td>6202 ZZ</td><td>Without Bearing Seal</td></tr> <tr><td>Lubrication interval</td><td>:</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>Lubricant amount</td><td>:</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>Lubricant type</td><td>:</td><td colspan="3" rowspan="5">Mobil Polyrex EM</td></tr> </table>					Bearing type	:	6203 ZZ	Drive end	Non drive end	Sealing	:	Without Bearing Seal	6202 ZZ	Without Bearing Seal	Lubrication interval	:	-	-	-	Lubricant amount	:	-	-	-	Lubricant type	:	Mobil Polyrex EM																																																																					
Bearing type	:	6203 ZZ	Drive end	Non drive end																																																																																												
Sealing	:	Without Bearing Seal	6202 ZZ	Without Bearing Seal																																																																																												
Lubrication interval	:	-	-	-																																																																																												
Lubricant amount	:	-	-	-																																																																																												
Lubricant type	:	Mobil Polyrex EM																																																																																														
Notes:																																																																																																
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>					These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																																																																											
Rev.	Changes Summary				Performed	Checked	Date																																																																																									
Performed by						Page		Revision																																																																																								
Checked by																																																																																																
Date	27/03/2024																																																																																															