

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Standard Efficiency Three-Phase

Product code : 12630186

Catalog # : .7536ES3E56-S

Frame : 56
 Output : 0.75 HP (0.55 kW)
 Poles : 2
 Frequency : 60 Hz
 Rated voltage : 208-230/460 V
 Rated current : 2.50-2.26/1.13 A
 L. R. Amperes : 17.5-15.8/7.91 A
 LRC : 7.0x(Code K)
 No load current : 0.948-1.10/0.550 A
 Rated speed : 3475 rpm
 Slip : 3.47 %
 Rated torque : 1.13 ft.lb
 Locked rotor torque : 250 %
 Breakdown torque : 290 %
 Insulation class : F
 Service factor : 1.15
 Moment of inertia (J) : 0.0517 sq.ft.lb

Locked rotor time : 41s (cold) 23s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : -20°C to +40°C
 Altitude : 1000 m.a.s.l.
 Protection degree : IP55
 Cooling method : IC411 - TEFC
 Mounting : F-1
 Rotation¹ : Both (CW and CCW)
 Noise level² : 68.0 dB(A)
 Starting method : Direct On Line
 Approx. weight³ : 20.4 lb

Output	50%	75%	100%
Efficiency (%)	62.0 70.3	68.0 73.4	72.0 73.0
	68.1	72.8	73.9
Power Factor	0.70 0.77	0.79 0.86	0.85 0.91
	0.68	0.80	0.86

Foundation loads
 Max. traction : 26 lb
 Max. compression : 46 lb

	Drive end	Non drive end
Bearing type	6203 ZZ	6202 ZZ
Sealing	V'Ring	Without Bearing Seal
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
		Revision		