

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :															
Product line	: Rolled Steel NEMA Premium Efficiency Three-Phase	Product code :	12675417												
		Catalog # :	00512ET3H215T-S												
Frame	: 213/5T	Locked rotor time	: 54s (cold) 30s (hot)												
Output	: 5 HP (3.7 kW)	Temperature rise	: 80 K												
Poles	: 6	Duty cycle	: Cont.(S1)												
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C												
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.												
Rated current	: 5.39 A	Protection degree	: IP55												
L. R. Amperes	: 32.4 A	Cooling method	: IC411 - TEFC												
LRC	: 6.0x(Code H)	Mounting	: F-1												
No load current	: 2.73 A	Rotation ¹	: Both (CW and CCW)												
Rated speed	: 1175 rpm	Noise level ²	: 55.0 dB(A)												
Slip	: 2.08 %	Starting method	: Direct On Line												
Rated torque	: 22.3 ft.lb	Approx. weight ³	: 142 lb												
Locked rotor torque	: 220 %														
Breakdown torque	: 250 %														
Insulation class	: F														
Service factor	: 1.15														
Moment of inertia (J)	: 1.26 sq.ft.lb														
Design	: B														
Output	50%	75%	100%												
Efficiency (%)	87.5	88.5	89.5												
Power Factor	0.59	0.71	0.77												
Foundation loads															
		Max. traction	: 244 lb												
		Max. compression	: 386 lb												
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33%; text-align: center; padding-bottom: 5px;">Drive end</td> <td style="width: 33%; text-align: center; padding-bottom: 5px;">Non drive end</td> </tr> <tr> <td>Bearing type : 6208 ZZ</td> <td>6206 ZZ</td> </tr> <tr> <td>Sealing : V'Ring</td> <td>Without Bearing Seal</td> </tr> <tr> <td>Lubrication interval : -</td> <td>-</td> </tr> <tr> <td>Lubricant amount : -</td> <td>-</td> </tr> <tr> <td>Lubricant type : Mobil Polyrex EM</td> <td></td> </tr> </table>				Drive end	Non drive end	Bearing type : 6208 ZZ	6206 ZZ	Sealing : V'Ring	Without Bearing Seal	Lubrication interval : -	-	Lubricant amount : -	-	Lubricant type : Mobil Polyrex EM	
Drive end	Non drive end														
Bearing type : 6208 ZZ	6206 ZZ														
Sealing : V'Ring	Without Bearing Seal														
Lubrication interval : -	-														
Lubricant amount : -	-														
Lubricant type : Mobil Polyrex EM															
Notes:															
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.													
Rev.	Changes Summary		Performed	Checked	Date										
Performed by															
Checked by				Page	Revision										
Date	27/03/2024			1 / 1											