

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium Efficiency
Three-Phase

Product code : 12692798

Catalog # : 02018ET3E256T-S

Frame : 254/6T
Output : 20 HP (15 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 49.4/24.7 A
L. R. Amperes : 331/165 A
LRC : 6.7x(Code H)
No load current : 22.2/11.1 A
Rated speed : 1765 rpm
Slip : 1.94 %
Rated torque : 59.5 ft.lb
Locked rotor torque : 270 %
Breakdown torque : 300 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 2.64 sq.ft.lb
Design : B

Locked rotor time : 28s (cold) 16s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 68.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 241 lb

Output	50%	75%	100%
Efficiency (%)	91.7	92.4	93.0
Power Factor	0.66	0.77	0.82

Foundation loads
Max. traction : 735 lb
Max. compression : 977 lb

	Drive end	Non drive end
Bearing type	6309 Z C3	6208 Z C3
Sealing	V'Ring	Without Bearing Seal
Lubrication interval	20000 h	20000 h
Lubricant amount	13 g	8 g
Lubricant type	Mobil Polyrex EM	

Notes:
USABLE @208V 54.6A SF 1.00 SFA 54.6A

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 1		
Checked by				
Date	27/03/2024			