

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																																																																																														
Product line		: Rolled Steel NEMA Premium Efficiency Three-Phase		Product code : 13322310																																																																																										
				Catalog # : 00736OT3ER184TC-S																																																																																										
<table> <tr><td>Frame</td><td>:</td><td>182/4TC</td><td>Locked rotor time</td><td>: 21s (cold) 12s (hot)</td></tr> <tr><td>Output</td><td>:</td><td>7.5 HP (5.5 kW)</td><td>Temperature rise</td><td>: 80 K</td></tr> <tr><td>Poles</td><td>:</td><td>2</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>:</td><td>60 Hz</td><td>Ambient temperature</td><td>: -20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>:</td><td>230/460 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>:</td><td>17.9/8.97 A</td><td>Cooling method</td><td>: IC01 - ODP</td></tr> <tr><td>L. R. Amperes</td><td>:</td><td>133/66.4 A</td><td>Mounting</td><td>: W-6</td></tr> <tr><td>LRC</td><td>:</td><td>7.4x(Code H)</td><td>Rotation¹</td><td>: Both (CW and CCW)</td></tr> <tr><td>No load current</td><td>:</td><td>7.80/3.90 A</td><td>Noise level²</td><td>: 65.0 dB(A)</td></tr> <tr><td>Rated speed</td><td>:</td><td>3500 rpm</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Slip</td><td>:</td><td>2.78 %</td><td>Approx. weight³</td><td>: 77.5 lb</td></tr> <tr><td>Rated torque</td><td>:</td><td>11.3 ft.lb</td><td></td><td></td></tr> <tr><td>Locked rotor torque</td><td>:</td><td>200 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>:</td><td>300 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>:</td><td>F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>:</td><td>1.15</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>:</td><td>0.1818 sq.ft.lb</td><td></td><td></td></tr> <tr><td>Design</td><td>:</td><td>B</td><td></td><td></td></tr> </table>				Frame	:	182/4TC	Locked rotor time	: 21s (cold) 12s (hot)	Output	:	7.5 HP (5.5 kW)	Temperature rise	: 80 K	Poles	:	2	Duty cycle	: Cont.(S1)	Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C	Rated voltage	:	230/460 V	Altitude	: 1000 m.a.s.l.	Rated current	:	17.9/8.97 A	Cooling method	: IC01 - ODP	L. R. Amperes	:	133/66.4 A	Mounting	: W-6	LRC	:	7.4x(Code H)	Rotation ¹	: Both (CW and CCW)	No load current	:	7.80/3.90 A	Noise level ²	: 65.0 dB(A)	Rated speed	:	3500 rpm	Starting method	: Direct On Line	Slip	:	2.78 %	Approx. weight ³	: 77.5 lb	Rated torque	:	11.3 ft.lb			Locked rotor torque	:	200 %			Breakdown torque	:	300 %			Insulation class	:	F			Service factor	:	1.15			Moment of inertia (J)	:	0.1818 sq.ft.lb			Design	:	B			
Frame	:	182/4TC	Locked rotor time	: 21s (cold) 12s (hot)																																																																																										
Output	:	7.5 HP (5.5 kW)	Temperature rise	: 80 K																																																																																										
Poles	:	2	Duty cycle	: Cont.(S1)																																																																																										
Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C																																																																																										
Rated voltage	:	230/460 V	Altitude	: 1000 m.a.s.l.																																																																																										
Rated current	:	17.9/8.97 A	Cooling method	: IC01 - ODP																																																																																										
L. R. Amperes	:	133/66.4 A	Mounting	: W-6																																																																																										
LRC	:	7.4x(Code H)	Rotation ¹	: Both (CW and CCW)																																																																																										
No load current	:	7.80/3.90 A	Noise level ²	: 65.0 dB(A)																																																																																										
Rated speed	:	3500 rpm	Starting method	: Direct On Line																																																																																										
Slip	:	2.78 %	Approx. weight ³	: 77.5 lb																																																																																										
Rated torque	:	11.3 ft.lb																																																																																												
Locked rotor torque	:	200 %																																																																																												
Breakdown torque	:	300 %																																																																																												
Insulation class	:	F																																																																																												
Service factor	:	1.15																																																																																												
Moment of inertia (J)	:	0.1818 sq.ft.lb																																																																																												
Design	:	B																																																																																												
Output	25%	50%	75%	100%	Foundation loads																																																																																									
Efficiency (%)	88.3	88.5	88.5	88.5	Max. traction : 177 lb																																																																																									
Power Factor	0.44	0.72	0.82	0.87	Max. compression : 254 lb																																																																																									
<table> <tr><td colspan="2">Bearing type</td><td>Drive end</td><td colspan="2">Non drive end</td></tr> <tr><td colspan="2">:</td><td>6206 ZZ</td><td colspan="2">6205 ZZ</td></tr> <tr><td colspan="2">Sealing</td><td>Without Bearing Seal</td><td colspan="2">Without Bearing Seal</td></tr> <tr><td colspan="2">Lubrication interval</td><td>-</td><td colspan="2">-</td></tr> <tr><td colspan="2">Lubricant amount</td><td>-</td><td colspan="2">-</td></tr> <tr><td colspan="2">Lubricant type</td><td>Mobil Polyrex EM</td><td colspan="2" rowspan="3"></td></tr> </table>					Bearing type		Drive end	Non drive end		:		6206 ZZ	6205 ZZ		Sealing		Without Bearing Seal	Without Bearing Seal		Lubrication interval		-	-		Lubricant amount		-	-		Lubricant type		Mobil Polyrex EM																																																														
Bearing type		Drive end	Non drive end																																																																																											
:		6206 ZZ	6205 ZZ																																																																																											
Sealing		Without Bearing Seal	Without Bearing Seal																																																																																											
Lubrication interval		-	-																																																																																											
Lubricant amount		-	-																																																																																											
Lubricant type		Mobil Polyrex EM																																																																																												
<p>Notes: USABLE @208V 19.2A SF 1.00 SFA 19.2A</p>																																																																																														
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.</p>					These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																																																																									
Rev.	Changes Summary			Performed	Checked	Date																																																																																								
Performed by					Page	Revision																																																																																								
Checked by																																																																																														
Date	27/03/2024				1 / 1																																																																																									
Customer :																																																																																														
Product line		: Rolled Steel NEMA Premium Efficiency Three-Phase		Product code : 13322310																																																																																										
				Catalog # : 00736OT3ER184TC-S																																																																																										
<table> <tr><td>Frame</td><td>:</td><td>182/4TC</td><td>Locked rotor time</td><td>: 21s (cold) 12s (hot)</td></tr> <tr><td>Output</td><td>:</td><td>7.5 HP (5.5 kW)</td><td>Temperature rise</td><td>: 80 K</td></tr> <tr><td>Poles</td><td>:</td><td>2</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>:</td><td>60 Hz</td><td>Ambient temperature</td><td>: -20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>:</td><td>230/460 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>:</td><td>17.9/8.97 A</td><td>Cooling method</td><td>: IC01 - ODP</td></tr> <tr><td>L. R. Amperes</td><td>:</td><td>133/66.4 A</td><td>Mounting</td><td>: W-6</td></tr> <tr><td>LRC</td><td>:</td><td>7.4x(Code H)</td><td>Rotation¹</td><td>: Both (CW and CCW)</td></tr> <tr><td>No load current</td><td>:</td><td>7.80/3.90 A</td><td>Noise level²</td><td>: 65.0 dB(A)</td></tr> <tr><td>Rated speed</td><td>:</td><td>3500 rpm</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Slip</td><td>:</td><td>2.78 %</td><td>Approx. weight³</td><td>: 77.5 lb</td></tr> <tr><td>Rated torque</td><td>:</td><td>11.3 ft.lb</td><td></td><td></td></tr> <tr><td>Locked rotor torque</td><td>:</td><td>200 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>:</td><td>300 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>:</td><td>F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>:</td><td>1.15</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>:</td><td>0.1818 sq.ft.lb</td><td></td><td></td></tr> <tr><td>Design</td><td>:</td><td>B</td><td></td><td></td></tr> </table>				Frame	:	182/4TC	Locked rotor time	: 21s (cold) 12s (hot)	Output	:	7.5 HP (5.5 kW)	Temperature rise	: 80 K	Poles	:	2	Duty cycle	: Cont.(S1)	Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C	Rated voltage	:	230/460 V	Altitude	: 1000 m.a.s.l.	Rated current	:	17.9/8.97 A	Cooling method	: IC01 - ODP	L. R. Amperes	:	133/66.4 A	Mounting	: W-6	LRC	:	7.4x(Code H)	Rotation ¹	: Both (CW and CCW)	No load current	:	7.80/3.90 A	Noise level ²	: 65.0 dB(A)	Rated speed	:	3500 rpm	Starting method	: Direct On Line	Slip	:	2.78 %	Approx. weight ³	: 77.5 lb	Rated torque	:	11.3 ft.lb			Locked rotor torque	:	200 %			Breakdown torque	:	300 %			Insulation class	:	F			Service factor	:	1.15			Moment of inertia (J)	:	0.1818 sq.ft.lb			Design	:	B			
Frame	:	182/4TC	Locked rotor time	: 21s (cold) 12s (hot)																																																																																										
Output	:	7.5 HP (5.5 kW)	Temperature rise	: 80 K																																																																																										
Poles	:	2	Duty cycle	: Cont.(S1)																																																																																										
Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C																																																																																										
Rated voltage	:	230/460 V	Altitude	: 1000 m.a.s.l.																																																																																										
Rated current	:	17.9/8.97 A	Cooling method	: IC01 - ODP																																																																																										
L. R. Amperes	:	133/66.4 A	Mounting	: W-6																																																																																										
LRC	:	7.4x(Code H)	Rotation ¹	: Both (CW and CCW)																																																																																										
No load current	:	7.80/3.90 A	Noise level ²	: 65.0 dB(A)																																																																																										
Rated speed	:	3500 rpm	Starting method	: Direct On Line																																																																																										
Slip	:	2.78 %	Approx. weight ³	: 77.5 lb																																																																																										
Rated torque	:	11.3 ft.lb																																																																																												
Locked rotor torque	:	200 %																																																																																												
Breakdown torque	:	300 %																																																																																												
Insulation class	:	F																																																																																												
Service factor	:	1.15																																																																																												
Moment of inertia (J)	:	0.1818 sq.ft.lb																																																																																												
Design	:	B																																																																																												
Output	25%	50%	75%	100%	Foundation loads																																																																																									
Efficiency (%)	88.3	88.5	88.5	88.5	Max. traction : 177 lb																																																																																									
Power Factor	0.44	0.72	0.82	0.87	Max. compression : 254 lb																																																																																									
<table> <tr><td colspan="2">Bearing type</td><td>Drive end</td><td colspan="2">Non drive end</td></tr> <tr><td colspan="2">:</td><td>6206 ZZ</td><td colspan="2">6205 ZZ</td></tr> <tr><td colspan="2">Sealing</td><td>Without Bearing Seal</td><td colspan="2">Without Bearing Seal</td></tr> <tr><td colspan="2">Lubrication interval</td><td>-</td><td colspan="2">-</td></tr> <tr><td colspan="2">Lubricant amount</td><td>-</td><td colspan="2">-</td></tr> <tr><td colspan="2">Lubricant type</td><td>Mobil Polyrex EM</td><td colspan="2" rowspan="3"></td></tr> </table>					Bearing type		Drive end	Non drive end		:		6206 ZZ	6205 ZZ		Sealing		Without Bearing Seal	Without Bearing Seal		Lubrication interval		-	-		Lubricant amount		-	-		Lubricant type		Mobil Polyrex EM																																																														
Bearing type		Drive end	Non drive end																																																																																											
:		6206 ZZ	6205 ZZ																																																																																											
Sealing		Without Bearing Seal	Without Bearing Seal																																																																																											
Lubrication interval		-	-																																																																																											
Lubricant amount		-	-																																																																																											
Lubricant type		Mobil Polyrex EM																																																																																												
<p>Notes: USABLE @208V 19.2A SF 1.00 SFA 19.2A</p>																																																																																														
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.</p>					These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																																																																									
Rev.	Changes Summary			Performed	Checked	Date																																																																																								
Performed by					Page	Revision																																																																																								
Checked by																																																																																														
Date	27/03/2024				1 / 1																																																																																									