

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																																																
Product line	: W22 NEMA Premium Efficiency Three-Phase			Product code :	12438117																																											
				Catalog # :	00118ET3H143T-W22																																											
Frame	: 143/5T	Locked rotor time	: 32s (cold) 18s (hot)																																													
Output	: 1 HP (0.75 kW)	Temperature rise	: 80 K																																													
Poles	: 4	Duty cycle	: Cont.(S1)																																													
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C																																													
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.																																													
Rated current	: 1.18 A	Protection degree	: IP55																																													
L. R. Amperes	: 10.1 A	Cooling method	: IC411 - TEFC																																													
LRC	: 8.6x(Code M)	Mounting	: F-1																																													
No load current	: 0.752 A	Rotation ¹	: Both (CW and CCW)																																													
Rated speed	: 1760 rpm	Noise level ²	: 51.0 dB(A)																																													
Slip	: 2.22 %	Starting method	: Direct On Line																																													
Rated torque	: 2.98 ft.lb	Approx. weight ³	: 43.8 lb																																													
Locked rotor torque	: 290 %																																															
Breakdown torque	: 350 %																																															
Insulation class	: F																																															
Service factor	: 1.25																																															
Moment of inertia (J)	: 0.1172 sq.ft.lb																																															
Design	: B																																															
Output	50%	75%	100%	Foundation loads																																												
Efficiency (%)	80.0	84.0	85.5	Max. traction	: 69 lb																																											
Power Factor	0.55	0.68	0.75	Max. compression	: 113 lb																																											
Losses at normative operating points (speed;torque), in percentage of rated output power																																																
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)																																										
15.9	12.8	12.5	10.1	7.0	5.8	4.3																																										
<table border="0"> <tr> <td></td><td style="text-align: center;">Drive end</td><td style="text-align: center;">Non drive end</td><td></td><td></td><td></td><td></td></tr> <tr> <td>Bearing type</td><td>: 6205 ZZ</td><td>: 6204 ZZ</td><td></td><td></td><td></td><td></td></tr> <tr> <td>Sealing</td><td>: V'Ring</td><td>: V'Ring</td><td></td><td></td><td></td><td></td></tr> <tr> <td>Lubrication interval</td><td>: -</td><td>: -</td><td></td><td></td><td></td><td></td></tr> <tr> <td>Lubricant amount</td><td>: -</td><td>: -</td><td></td><td></td><td></td><td></td></tr> <tr> <td>Lubricant type</td><td>: Mobil Polyrex EM</td><td></td><td></td><td></td><td></td><td></td></tr> </table>								Drive end	Non drive end					Bearing type	: 6205 ZZ	: 6204 ZZ					Sealing	: V'Ring	: V'Ring					Lubrication interval	: -	: -					Lubricant amount	: -	: -					Lubricant type	: Mobil Polyrex EM					
	Drive end	Non drive end																																														
Bearing type	: 6205 ZZ	: 6204 ZZ																																														
Sealing	: V'Ring	: V'Ring																																														
Lubrication interval	: -	: -																																														
Lubricant amount	: -	: -																																														
Lubricant type	: Mobil Polyrex EM																																															
Notes:																																																
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																												
Rev.	Changes Summary			Performed	Checked	Date																																										
Performed by					Page	Revision																																										
Checked by																																																
Date	26/03/2024				1 / 1																																											