

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line	: W22 Single-Phase			Product code :	13876938
				Catalog # :	00318ES1E184T-W22
Frame	: 182/4T	Locked rotor time	: 14s (cold) 8s (hot)		
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K		
Poles	: 4	Duty cycle	: Cont.(S1)		
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C		
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.		
Rated current	: 14.5-13.8/6.90 A	Protection degree	: IP55		
L. R. Amperes	: 112-106/53.1 A	Cooling method	: IC411 - TEFC		
LRC	: 7.7x(Code K)	Mounting	: F-1		
No load current	: 5.78-6.70/3.35 A	Rotation ¹	: Both (CW and CCW)		
Rated speed	: 1745 rpm	Noise level ²	: 60.0 dB(A)		
Slip	: 3.06 %	Starting method	: Direct On Line		
Rated torque	: 9.03 ft.lb	Approx. weight ³	: 106 lb		
Locked rotor torque	: 290 %				
Breakdown torque	: 270 %				
Insulation class	: F				
Service factor	: 1.15				
Moment of inertia (J)	: 0.3735 sq.ft.lb				

Output	50%	75%	100%	Foundation loads
Efficiency (%)	65.0	74.0	77.0	Max. traction : 103 lb
Power Factor	0.79	0.87	0.90	Max. compression : 208 lb

	Drive end	Non drive end
Bearing type	: 6207 ZZ	6206 ZZ
Sealing	: V'Ring	V'Ring
Lubrication interval	: -	-
Lubricant amount	: -	-
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	28/03/2024				
				Page	Revision
				1 / 1	