

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																																																
Product line	: W22 NEMA Premium Efficiency Three-Phase			Product code :	11165718																																											
				Catalog # :	10036ET3H405TS-W22																																											
Frame	: 404/5TS	Locked rotor time	: 25s (cold) 14s (hot)																																													
Output	: 100 HP (75 kW)	Temperature rise	: 80 K																																													
Poles	: 2	Duty cycle	: Cont.(S1)																																													
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C																																													
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.																																													
Rated current	: 89.6 A	Protection degree	: IP55																																													
L. R. Amperes	: 582 A	Cooling method	: IC411 - TEFC																																													
LRC	: 6.5x(Code G)	Mounting	: F-1																																													
No load current	: 20.8 A	Rotation ¹	: Both (CW and CCW)																																													
Rated speed	: 3545 rpm	Noise level ²	: 79.0 dB(A)																																													
Slip	: 1.53 %	Starting method	: Direct On Line																																													
Rated torque	: 148 ft.lb	Approx. weight ³	: 1065 lb																																													
Locked rotor torque	: 240 %																																															
Breakdown torque	: 260 %																																															
Insulation class	: F																																															
Service factor	: 1.25																																															
Moment of inertia (J)	: 13.2 sq.ft.lb																																															
Design	: B																																															
Output	25%	50%	75%	100%	Foundation loads																																											
Efficiency (%)	92.8	93.0	94.1	94.1	Max. traction	: 623 lb																																										
Power Factor	0.61	0.83	0.88	0.89	Max. compression	: 1688 lb																																										
Losses at normative operating points (speed;torque), in percentage of rated output power																																																
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)																																										
5.9	4.6	4.4	2.8	1.6	0.9	0.5																																										
<table border="0"> <thead> <tr> <th colspan="3">Drive end</th> <th colspan="4">Non drive end</th> </tr> </thead> <tbody> <tr> <td>Bearing type</td><td>:</td><td>6314 C3</td><td></td><td></td><td>6314 C3</td><td></td></tr> <tr> <td>Sealing</td><td>:</td><td>WSeal</td><td></td><td></td><td>WSeal</td><td></td></tr> <tr> <td>Lubrication interval</td><td>:</td><td>4000 h</td><td></td><td></td><td>4000 h</td><td></td></tr> <tr> <td>Lubricant amount</td><td>:</td><td>27 g</td><td></td><td></td><td>27 g</td><td></td></tr> <tr> <td>Lubricant type</td><td>:</td><td colspan="5" rowspan="2">Mobil Polyrex EM</td></tr> </tbody> </table>							Drive end			Non drive end				Bearing type	:	6314 C3			6314 C3		Sealing	:	WSeal			WSeal		Lubrication interval	:	4000 h			4000 h		Lubricant amount	:	27 g			27 g		Lubricant type	:	Mobil Polyrex EM				
Drive end			Non drive end																																													
Bearing type	:	6314 C3			6314 C3																																											
Sealing	:	WSeal			WSeal																																											
Lubrication interval	:	4000 h			4000 h																																											
Lubricant amount	:	27 g			27 g																																											
Lubricant type	:	Mobil Polyrex EM																																														
Notes:																																																
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>				<p>These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.</p>																																												
Rev.	Changes Summary			Performed	Checked	Date																																										
Performed by					Page	Revision																																										
Checked by																																																
Date	26/03/2024				1 / 1																																											
Customer :																																																
Product line	: W22 NEMA Premium Efficiency Three-Phase			Product code :	11165718																																											
				Catalog # :	10036ET3H405TS-W22																																											
Frame	: 404/5TS	Locked rotor time	: 25s (cold) 14s (hot)																																													
Output	: 100 HP (75 kW)	Temperature rise	: 80 K																																													
Poles	: 2	Duty cycle	: Cont.(S1)																																													
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C																																													
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.																																													
Rated current	: 89.6 A	Protection degree	: IP55																																													
L. R. Amperes	: 582 A	Cooling method	: IC411 - TEFC																																													
LRC	: 6.5x(Code G)	Mounting	: F-1																																													
No load current	: 20.8 A	Rotation ¹	: Both (CW and CCW)																																													
Rated speed	: 3545 rpm	Noise level ²	: 79.0 dB(A)																																													
Slip	: 1.53 %	Starting method	: Direct On Line																																													
Rated torque	: 148 ft.lb	Approx. weight ³	: 1065 lb																																													
Locked rotor torque	: 240 %																																															
Breakdown torque	: 260 %																																															
Insulation class	: F																																															
Service factor	: 1.25																																															
Moment of inertia (J)	: 13.2 sq.ft.lb																																															
Design	: B																																															
Output	25%	50%	75%	100%	Foundation loads																																											
Efficiency (%)	92.8	93.0	94.1	94.1	Max. traction	: 623 lb																																										
Power Factor	0.61	0.83	0.88	0.89	Max. compression	: 1688 lb																																										
Losses at normative operating points (speed;torque), in percentage of rated output power																																																
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)																																										
5.9	4.6	4.4	2.8	1.6	0.9	0.5																																										
<table border="0"> <thead> <tr> <th colspan="3">Drive end</th> <th colspan="4">Non drive end</th> </tr> </thead> <tbody> <tr> <td>Bearing type</td><td>:</td><td>6314 C3</td><td></td><td></td><td>6314 C3</td><td></td></tr> <tr> <td>Sealing</td><td>:</td><td>WSeal</td><td></td><td></td><td>WSeal</td><td></td></tr> <tr> <td>Lubrication interval</td><td>:</td><td>4000 h</td><td></td><td></td><td>4000 h</td><td></td></tr> <tr> <td>Lubricant amount</td><td>:</td><td>27 g</td><td></td><td></td><td>27 g</td><td></td></tr> <tr> <td>Lubricant type</td><td>:</td><td colspan="5" rowspan="2">Mobil Polyrex EM</td></tr> </tbody> </table>							Drive end			Non drive end				Bearing type	:	6314 C3			6314 C3		Sealing	:	WSeal			WSeal		Lubrication interval	:	4000 h			4000 h		Lubricant amount	:	27 g			27 g		Lubricant type	:	Mobil Polyrex EM				
Drive end			Non drive end																																													
Bearing type	:	6314 C3			6314 C3																																											
Sealing	:	WSeal			WSeal																																											
Lubrication interval	:	4000 h			4000 h																																											
Lubricant amount	:	27 g			27 g																																											
Lubricant type	:	Mobil Polyrex EM																																														
Notes:																																																
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>				<p>These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.</p>																																												
Rev.	Changes Summary			Performed	Checked	Date																																										
Performed by					Page	Revision																																										
Checked by																																																
Date	26/03/2024				1 / 1																																											