

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																																																																											
Product line		: Rolled Steel Premium Efficiency Three-Phase		Product code : 14014000																																																																							
				Catalog # : 00118OT3J56-S																																																																							
<table> <tr><td>Frame</td><td>: 56</td><td>Locked rotor time</td><td>: 30s (cold) 17s (hot)</td></tr> <tr><td>Output</td><td>: 1 HP (0.75 kW)</td><td>Temperature rise</td><td>: 70 K</td></tr> <tr><td>Poles</td><td>: 4</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>: 60 Hz</td><td>Ambient temperature</td><td>: -20°C to +50°C</td></tr> <tr><td>Rated voltage</td><td>: 380/660 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>: 1.90/1.09 A</td><td>Cooling method</td><td>: IC01 - ODP</td></tr> <tr><td>L. R. Amperes</td><td>: 14.4/8.28 A</td><td>Mounting</td><td>: F-1</td></tr> <tr><td>LRC</td><td>: 7.6x(Code L)</td><td>Rotation¹</td><td>: Both (CW and CCW)</td></tr> <tr><td>No load current</td><td>: 1.33/0.767 A</td><td>Noise level²</td><td>: 52.0 dB(A)</td></tr> <tr><td>Rated speed</td><td>: 1760 rpm</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Slip</td><td>: 2.22 %</td><td>Approx. weight³</td><td>: 26.9 lb</td></tr> <tr><td>Rated torque</td><td>: 2.98 ft.lb</td><td></td><td></td></tr> <tr><td>Locked rotor torque</td><td>: 280 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>: 320 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>: F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>: 1.15</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>: 0.0854 sq.ft.lb</td><td></td><td></td></tr> <tr><td>Design</td><td>: A</td><td></td><td></td></tr> </table>				Frame	: 56	Locked rotor time	: 30s (cold) 17s (hot)	Output	: 1 HP (0.75 kW)	Temperature rise	: 70 K	Poles	: 4	Duty cycle	: Cont.(S1)	Frequency	: 60 Hz	Ambient temperature	: -20°C to +50°C	Rated voltage	: 380/660 V	Altitude	: 1000 m.a.s.l.	Rated current	: 1.90/1.09 A	Cooling method	: IC01 - ODP	L. R. Amperes	: 14.4/8.28 A	Mounting	: F-1	LRC	: 7.6x(Code L)	Rotation ¹	: Both (CW and CCW)	No load current	: 1.33/0.767 A	Noise level ²	: 52.0 dB(A)	Rated speed	: 1760 rpm	Starting method	: Direct On Line	Slip	: 2.22 %	Approx. weight ³	: 26.9 lb	Rated torque	: 2.98 ft.lb			Locked rotor torque	: 280 %			Breakdown torque	: 320 %			Insulation class	: F			Service factor	: 1.15			Moment of inertia (J)	: 0.0854 sq.ft.lb			Design	: A		
Frame	: 56	Locked rotor time	: 30s (cold) 17s (hot)																																																																								
Output	: 1 HP (0.75 kW)	Temperature rise	: 70 K																																																																								
Poles	: 4	Duty cycle	: Cont.(S1)																																																																								
Frequency	: 60 Hz	Ambient temperature	: -20°C to +50°C																																																																								
Rated voltage	: 380/660 V	Altitude	: 1000 m.a.s.l.																																																																								
Rated current	: 1.90/1.09 A	Cooling method	: IC01 - ODP																																																																								
L. R. Amperes	: 14.4/8.28 A	Mounting	: F-1																																																																								
LRC	: 7.6x(Code L)	Rotation ¹	: Both (CW and CCW)																																																																								
No load current	: 1.33/0.767 A	Noise level ²	: 52.0 dB(A)																																																																								
Rated speed	: 1760 rpm	Starting method	: Direct On Line																																																																								
Slip	: 2.22 %	Approx. weight ³	: 26.9 lb																																																																								
Rated torque	: 2.98 ft.lb																																																																										
Locked rotor torque	: 280 %																																																																										
Breakdown torque	: 320 %																																																																										
Insulation class	: F																																																																										
Service factor	: 1.15																																																																										
Moment of inertia (J)	: 0.0854 sq.ft.lb																																																																										
Design	: A																																																																										
Output	25%	50%	75%	100%																																																																							
Efficiency (%)	0.000	78.5	82.5	83.5																																																																							
Power Factor	0.00	0.49	0.63	0.72																																																																							
<table> <tr> <td colspan="2"></td><td>Drive end</td><td colspan="2">Non drive end</td></tr> <tr> <td colspan="2">Bearing type</td><td>: 6204 ZZ</td><td colspan="2">6202 ZZ</td></tr> <tr> <td colspan="2">Sealing</td><td>: Without Bearing Seal</td><td colspan="2">Without Bearing Seal</td></tr> <tr> <td colspan="2">Lubrication interval</td><td>: 0 h</td><td colspan="2">0 h</td></tr> <tr> <td colspan="2">Lubricant amount</td><td>: 0 g</td><td colspan="2" rowspan="3">0 g</td></tr> <tr> <td colspan="2">Lubricant type</td><td colspan="3" rowspan="2">Mobil Polyrex EM</td></tr> </table>							Drive end	Non drive end		Bearing type		: 6204 ZZ	6202 ZZ		Sealing		: Without Bearing Seal	Without Bearing Seal		Lubrication interval		: 0 h	0 h		Lubricant amount		: 0 g	0 g		Lubricant type		Mobil Polyrex EM																																											
		Drive end	Non drive end																																																																								
Bearing type		: 6204 ZZ	6202 ZZ																																																																								
Sealing		: Without Bearing Seal	Without Bearing Seal																																																																								
Lubrication interval		: 0 h	0 h																																																																								
Lubricant amount		: 0 g	0 g																																																																								
Lubricant type		Mobil Polyrex EM																																																																									
Notes:																																																																											
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>			<p>These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.</p>																																																																								
Rev.	Changes Summary			Performed																																																																							
				Checked																																																																							
Performed by				Page																																																																							
Checked by				Revision																																																																							
Date	27/03/2024			1 / 1																																																																							