

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																							
Product line	: W22 High Efficiency Three-Phase		Product code :	12823176																			
Frame : 184TC Output : 5 HP (3.7 kW) Poles : 2 Frequency : 60 Hz Rated voltage : 230/460 V Rated current : 11.8/5.90 A L. R. Amperes : 86.1/43.1 A LRC : 7.3x(Code H) No load current : 4.20/2.10 A Rated speed : 3490 rpm Slip : 3.06 % Rated torque : 7.52 ft.lb Locked rotor torque : 200 % Breakdown torque : 300 % Insulation class : F Service factor : 1.25 Moment of inertia (J) : 0.1906 sq.ft.lb Design : B		Locked rotor time : 48s (cold) 27s (hot) Temperature rise : 80 K Duty cycle : Cont.(S1) Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Protection degree : IP55 Cooling method : IC411 - TEFC Mounting : W-6 Rotation ¹ : Both (CW and CCW) Noise level ² : 70.0 dB(A) Starting method : Direct On Line Approx. weight ³ : 95.8 lb																					
Output	25%	50%	75%	100%																			
Efficiency (%)	85.1	87.1	85.5	86.5																			
	87.0	87.0	86.5	86.5																			
Power Factor	0.51	0.57	0.78	0.82																			
	0.54	0.51	0.80	0.78																			
Losses at normative operating points (speed;torque), in percentage of rated output power																							
Losses (%)	P1 (0,9;1,0)	13.5	16.0	14.7	14.7																		
	P2 (0,5;1,0)	10.8	12.8	11.8	11.8																		
	P3 (0,25;1,0)	10.2	12.1	11.2	11.2																		
	P4 (0,9;0,5)	7.0	8.3	7.6	7.6																		
	P5 (0,5;0,5)	4.1	4.8	4.4	4.4																		
	P6 (0,5;0,25)	2.6	3.1	2.8	2.8																		
	P7 (0,25;0,25)	1.6	1.9	1.7	1.7																		
<table border="1"> <thead> <tr> <th></th><th>Drive end</th><th>Non drive end</th></tr> </thead> <tbody> <tr> <td>Bearing type</td><td>: 6207 ZZ</td><td>6206 ZZ</td></tr> <tr> <td>Sealing</td><td>: V'Ring</td><td>V'Ring</td></tr> <tr> <td>Lubrication interval</td><td>: -</td><td>-</td></tr> <tr> <td>Lubricant amount</td><td>: -</td><td>-</td></tr> <tr> <td>Lubricant type</td><td colspan="3" rowspan="2">Mobil Polyrex EM</td></tr> </tbody> </table>						Drive end	Non drive end	Bearing type	: 6207 ZZ	6206 ZZ	Sealing	: V'Ring	V'Ring	Lubrication interval	: -	-	Lubricant amount	: -	-	Lubricant type	Mobil Polyrex EM		
	Drive end	Non drive end																					
Bearing type	: 6207 ZZ	6206 ZZ																					
Sealing	: V'Ring	V'Ring																					
Lubrication interval	: -	-																					
Lubricant amount	: -	-																					
Lubricant type	Mobil Polyrex EM																						
Notes:																							
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																				
Rev.	Changes Summary			Performed																			
				Checked																			
Performed by				Page																			
Checked by				Revision																			
Date	29/03/2024			1 / 1																			