

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Premium Efficiency Three-Phase

Product code : 12809255

Catalog # : .7518OT3H56CFL-S

Frame : 56C
 Output : 0.75 HP (0.55 kW)
 Poles : 4
 Frequency : 60 Hz
 Rated voltage : 575 V
 Rated current : 0.920 A
 L. R. Amperes : 6.72 A
 LRC : 7.3x(Code K)
 No load current : 0.640 A
 Rated speed : 1760 rpm
 Slip : 2.22 %
 Rated torque : 2.24 ft.lb
 Locked rotor torque : 250 %
 Breakdown torque : 300 %
 Insulation class : F
 Service factor : 1.25
 Moment of inertia (J) : 0.0712 sq.ft.lb

Locked rotor time : 37s (cold) 21s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : -20°C to +40°C
 Altitude : 1000 m.a.s.l.
 Cooling method : IC01 - ODP
 Mounting : F-1
 Rotation¹ : Both (CW and CCW)
 Noise level² : 52.0 dB(A)
 Starting method : Direct On Line
 Approx. weight³ : 23.5 lb

Output	25%	50%	75%	100%
Efficiency (%)	71.6	74.0	78.5	81.1
Power Factor	0.29	0.52	0.65	0.74

Foundation loads
 Max. traction : 54 lb
 Max. compression : 77 lb

	Drive end	Non drive end
Bearing type :	6203 ZZ	6202 ZZ
Sealing :	Without Bearing Seal	Without Bearing Seal
Lubrication interval :	-	-
Lubricant amount :	-	-
Lubricant type :	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
		Revision		