

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																																																																																														
Product line		: Rolled Steel Premium Efficiency Three-Phase		Product code : 14014002																																																																																										
				Catalog # : 00158OT3J56-S																																																																																										
<table> <tr><td>Frame</td><td>:</td><td>56H</td><td>Locked rotor time</td><td>: 25s (cold) 14s (hot)</td></tr> <tr><td>Output</td><td>:</td><td>1.5 HP (1.1 kW)</td><td>Temperature rise</td><td>: 70 K</td></tr> <tr><td>Poles</td><td>:</td><td>4</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>:</td><td>60 Hz</td><td>Ambient temperature</td><td>: -20°C to +50°C</td></tr> <tr><td>Rated voltage</td><td>:</td><td>380/660 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>:</td><td>2.54/1.46 A</td><td>Cooling method</td><td>: IC01 - ODP</td></tr> <tr><td>L. R. Amperes</td><td>:</td><td>22.4/12.8 A</td><td>Mounting</td><td>: F-1</td></tr> <tr><td>LRC</td><td>:</td><td>8.8x(Code L)</td><td>Rotation¹</td><td>: Both (CW and CCW)</td></tr> <tr><td>No load current</td><td>:</td><td>1.57/0.906 A</td><td>Noise level²</td><td>: 52.0 dB(A)</td></tr> <tr><td>Rated speed</td><td>:</td><td>1760 rpm</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Slip</td><td>:</td><td>2.22 %</td><td>Approx. weight³</td><td>: 37.5 lb</td></tr> <tr><td>Rated torque</td><td>:</td><td>4.48 ft.lb</td><td></td><td></td></tr> <tr><td>Locked rotor torque</td><td>:</td><td>290 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>:</td><td>350 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>:</td><td>F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>:</td><td>1.15</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>:</td><td>0.1305 sq.ft.lb</td><td></td><td></td></tr> <tr><td>Design</td><td>:</td><td>A</td><td></td><td></td></tr> </table>				Frame	:	56H	Locked rotor time	: 25s (cold) 14s (hot)	Output	:	1.5 HP (1.1 kW)	Temperature rise	: 70 K	Poles	:	4	Duty cycle	: Cont.(S1)	Frequency	:	60 Hz	Ambient temperature	: -20°C to +50°C	Rated voltage	:	380/660 V	Altitude	: 1000 m.a.s.l.	Rated current	:	2.54/1.46 A	Cooling method	: IC01 - ODP	L. R. Amperes	:	22.4/12.8 A	Mounting	: F-1	LRC	:	8.8x(Code L)	Rotation ¹	: Both (CW and CCW)	No load current	:	1.57/0.906 A	Noise level ²	: 52.0 dB(A)	Rated speed	:	1760 rpm	Starting method	: Direct On Line	Slip	:	2.22 %	Approx. weight ³	: 37.5 lb	Rated torque	:	4.48 ft.lb			Locked rotor torque	:	290 %			Breakdown torque	:	350 %			Insulation class	:	F			Service factor	:	1.15			Moment of inertia (J)	:	0.1305 sq.ft.lb			Design	:	A			
Frame	:	56H	Locked rotor time	: 25s (cold) 14s (hot)																																																																																										
Output	:	1.5 HP (1.1 kW)	Temperature rise	: 70 K																																																																																										
Poles	:	4	Duty cycle	: Cont.(S1)																																																																																										
Frequency	:	60 Hz	Ambient temperature	: -20°C to +50°C																																																																																										
Rated voltage	:	380/660 V	Altitude	: 1000 m.a.s.l.																																																																																										
Rated current	:	2.54/1.46 A	Cooling method	: IC01 - ODP																																																																																										
L. R. Amperes	:	22.4/12.8 A	Mounting	: F-1																																																																																										
LRC	:	8.8x(Code L)	Rotation ¹	: Both (CW and CCW)																																																																																										
No load current	:	1.57/0.906 A	Noise level ²	: 52.0 dB(A)																																																																																										
Rated speed	:	1760 rpm	Starting method	: Direct On Line																																																																																										
Slip	:	2.22 %	Approx. weight ³	: 37.5 lb																																																																																										
Rated torque	:	4.48 ft.lb																																																																																												
Locked rotor torque	:	290 %																																																																																												
Breakdown torque	:	350 %																																																																																												
Insulation class	:	F																																																																																												
Service factor	:	1.15																																																																																												
Moment of inertia (J)	:	0.1305 sq.ft.lb																																																																																												
Design	:	A																																																																																												
Output	25%	50%	75%	100%	Foundation loads																																																																																									
Efficiency (%)	0.000	84.0	85.5	86.5	Max. traction	: 135 lb																																																																																								
Power Factor	0.00	0.53	0.66	0.76	Max. compression	: 172 lb																																																																																								
<table> <tr><td colspan="2">Bearing type</td><td>Drive end</td><td colspan="2">Non drive end</td></tr> <tr><td colspan="2">:</td><td>6204 ZZ</td><td colspan="2">6202 ZZ</td></tr> <tr><td colspan="2">Sealing</td><td>Without Bearing Seal</td><td colspan="2">Without Bearing Seal</td></tr> <tr><td colspan="2">Lubrication interval</td><td>0 h</td><td colspan="2">0 h</td></tr> <tr><td colspan="2">Lubricant amount</td><td>0 g</td><td colspan="2" rowspan="4">0 g</td></tr> <tr><td colspan="2">Lubricant type</td><td colspan="3" rowspan="3">Mobil Polyrex EM</td></tr> </table>					Bearing type		Drive end	Non drive end		:		6204 ZZ	6202 ZZ		Sealing		Without Bearing Seal	Without Bearing Seal		Lubrication interval		0 h	0 h		Lubricant amount		0 g	0 g		Lubricant type		Mobil Polyrex EM																																																														
Bearing type		Drive end	Non drive end																																																																																											
:		6204 ZZ	6202 ZZ																																																																																											
Sealing		Without Bearing Seal	Without Bearing Seal																																																																																											
Lubrication interval		0 h	0 h																																																																																											
Lubricant amount		0 g	0 g																																																																																											
Lubricant type		Mobil Polyrex EM																																																																																												
Notes:																																																																																														
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>					These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																																																																									
Rev.	Changes Summary			Performed	Checked	Date																																																																																								
Performed by					Page 1 / 1																																																																																									
Checked by																																																																																														
Date	27/03/2024																																																																																													