

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :																																																																											
Product line	: Rolled Steel Premium Efficiency Three-Phase		Product code :	15459818																																																																							
				Catalog # : 00218ET3H56CFL-S																																																																							
<table> <tr><td>Frame</td><td>: 56C</td><td>Locked rotor time</td><td>: 27s (cold) 15s (hot)</td></tr> <tr><td>Output</td><td>: 2 HP (1.5 kW)</td><td>Temperature rise</td><td>: 80 K</td></tr> <tr><td>Poles</td><td>: 4</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>: 60 Hz</td><td>Ambient temperature</td><td>: -20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>: 575 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>: 2.18 A</td><td>Protection degree</td><td>: IP55</td></tr> <tr><td>L. R. Amperes</td><td>: 17.8 A</td><td>Cooling method</td><td>: IC411 - TEFC</td></tr> <tr><td>LRC</td><td>: 8.2x(Code K)</td><td>Mounting</td><td>: F-1</td></tr> <tr><td>No load current</td><td>: 1.12 A</td><td>Rotation<sup>1</sup></td><td>: Both (CW and CCW)</td></tr> <tr><td>Rated speed</td><td>: 1745 rpm</td><td>Noise level<sup>2</sup></td><td>: 52.0 dB(A)</td></tr> <tr><td>Slip</td><td>: 3.06 %</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Rated torque</td><td>: 6.02 ft.lb</td><td>Approx. weight<sup>3</sup></td><td>: 41.2 lb</td></tr> <tr><td>Locked rotor torque</td><td>: 270 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>: 300 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>: F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>: 1.15</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>: 0.1296 sq.ft.lb</td><td></td><td></td></tr> <tr><td>Design</td><td>: B</td><td></td><td></td></tr> </table>				Frame	: 56C	Locked rotor time	: 27s (cold) 15s (hot)	Output	: 2 HP (1.5 kW)	Temperature rise	: 80 K	Poles	: 4	Duty cycle	: Cont.(S1)	Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C	Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.	Rated current	: 2.18 A	Protection degree	: IP55	L. R. Amperes	: 17.8 A	Cooling method	: IC411 - TEFC	LRC	: 8.2x(Code K)	Mounting	: F-1	No load current	: 1.12 A	Rotation <sup>1</sup>	: Both (CW and CCW)	Rated speed	: 1745 rpm	Noise level <sup>2</sup>	: 52.0 dB(A)	Slip	: 3.06 %	Starting method	: Direct On Line	Rated torque	: 6.02 ft.lb	Approx. weight <sup>3</sup>	: 41.2 lb	Locked rotor torque	: 270 %			Breakdown torque	: 300 %			Insulation class	: F			Service factor	: 1.15			Moment of inertia (J)	: 0.1296 sq.ft.lb			Design	: B		
Frame	: 56C	Locked rotor time	: 27s (cold) 15s (hot)																																																																								
Output	: 2 HP (1.5 kW)	Temperature rise	: 80 K																																																																								
Poles	: 4	Duty cycle	: Cont.(S1)																																																																								
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C																																																																								
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.																																																																								
Rated current	: 2.18 A	Protection degree	: IP55																																																																								
L. R. Amperes	: 17.8 A	Cooling method	: IC411 - TEFC																																																																								
LRC	: 8.2x(Code K)	Mounting	: F-1																																																																								
No load current	: 1.12 A	Rotation <sup>1</sup>	: Both (CW and CCW)																																																																								
Rated speed	: 1745 rpm	Noise level <sup>2</sup>	: 52.0 dB(A)																																																																								
Slip	: 3.06 %	Starting method	: Direct On Line																																																																								
Rated torque	: 6.02 ft.lb	Approx. weight <sup>3</sup>	: 41.2 lb																																																																								
Locked rotor torque	: 270 %																																																																										
Breakdown torque	: 300 %																																																																										
Insulation class	: F																																																																										
Service factor	: 1.15																																																																										
Moment of inertia (J)	: 0.1296 sq.ft.lb																																																																										
Design	: B																																																																										
Output	25%	50%	75%	100%																																																																							
Efficiency (%)	86.0	85.5	87.5	86.5																																																																							
Power Factor	0.35	0.60	0.73	0.80																																																																							
<table> <tr> <td colspan="2"></td><td>Drive end</td><td colspan="2">Non drive end</td></tr> <tr> <td colspan="2">Bearing type</td><td>: 6204 ZZ</td><td colspan="2">6202 ZZ</td></tr> <tr> <td colspan="2">Sealing</td><td>: V'Ring</td><td colspan="2">Without Bearing Seal</td></tr> <tr> <td colspan="2">Lubrication interval</td><td>: -</td><td colspan="2">-</td></tr> <tr> <td colspan="2">Lubricant amount</td><td>: -</td><td colspan="2">-</td></tr> <tr> <td colspan="2">Lubricant type</td><td>: Mobil Polyrex EM</td><td colspan="2" rowspan="3"></td></tr> </table>							Drive end	Non drive end		Bearing type		: 6204 ZZ	6202 ZZ		Sealing		: V'Ring	Without Bearing Seal		Lubrication interval		: -	-		Lubricant amount		: -	-		Lubricant type		: Mobil Polyrex EM																																											
		Drive end	Non drive end																																																																								
Bearing type		: 6204 ZZ	6202 ZZ																																																																								
Sealing		: V'Ring	Without Bearing Seal																																																																								
Lubrication interval		: -	-																																																																								
Lubricant amount		: -	-																																																																								
Lubricant type		: Mobil Polyrex EM																																																																									
Notes:																																																																											
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>																																																																											
Rev.	Changes Summary			Performed																																																																							
				Checked																																																																							
Performed by																																																																											
Checked by																																																																											
Date	27/03/2024																																																																										
			Page	Revision																																																																							
			1 / 1																																																																								