

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																						
Product line	: Rolled Steel Standard Efficiency Three-Phase		Product code :	12675955																		
			Catalog # :	00112OS3E56-S																		
Frame : 56H Output : 1 HP (0.75 kW) Poles : 6 Frequency : 60 Hz Rated voltage : 230/460 V Rated current : 3.40/1.70 A L. R. Amperes : 19.0/9.52 A LRC : 5.6x(Code J) No load current : 2.34/1.17 A Rated speed : 1145 rpm Slip : 4.58 % Rated torque : 4.59 ft.lb Locked rotor torque : 220 % Breakdown torque : 270 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 0.1419 sq.ft.lb Design : A		Locked rotor time : 28s (cold) 16s (hot) Temperature rise : 80 K Duty cycle : Cont.(S1) Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Cooling method : IC01 - ODP Mounting : F-1 Rotation ¹ : Both (CW and CCW) Noise level ² : 50.0 dB(A) Starting method : Direct On Line Approx. weight ³ : 33.2 lb																				
Output	25%	50%	75%	100%																		
Efficiency (%)	70.3	72.0	75.5	77.0																		
Power Factor	0.28	0.49	0.63	0.72																		
<table> <thead> <tr> <th></th><th>Drive end</th><th>Non drive end</th></tr> </thead> <tbody> <tr> <td>Bearing type</td><td>: 6204 ZZ</td><td>: 6202 ZZ</td></tr> <tr> <td>Sealing</td><td>: Without Bearing Seal</td><td>: Without Bearing Seal</td></tr> <tr> <td>Lubrication interval</td><td>: -</td><td>: -</td></tr> <tr> <td>Lubricant amount</td><td>: -</td><td>: -</td></tr> <tr> <td>Lubricant type</td><td colspan="2" rowspan="3">: Mobil Polyrex EM</td></tr> </tbody> </table>						Drive end	Non drive end	Bearing type	: 6204 ZZ	: 6202 ZZ	Sealing	: Without Bearing Seal	: Without Bearing Seal	Lubrication interval	: -	: -	Lubricant amount	: -	: -	Lubricant type	: Mobil Polyrex EM	
	Drive end	Non drive end																				
Bearing type	: 6204 ZZ	: 6202 ZZ																				
Sealing	: Without Bearing Seal	: Without Bearing Seal																				
Lubrication interval	: -	: -																				
Lubricant amount	: -	: -																				
Lubricant type	: Mobil Polyrex EM																					
Notes: USABLE @208V 3.76A SF 1.00 SFA 3.76A																						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																			
Rev.	Changes Summary			Performed																		
				Checked																		
Performed by				Page																		
Checked by				Revision																		
Date	27/03/2024			1 / 1																		