

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Standard Efficiency Three-Phase

Product code : 12895591

Catalog # : .3318ES3E56C-S

Frame : 56C
 Output : 0.33 HP (0.25 kW)
 Poles : 4
 Frequency : 60 Hz
 Rated voltage : 208-230/460 V
 Rated current : 1.38-1.25/0.624 A
 L. R. Amperes : 9.80-8.86/4.43 A
 LRC : 7.1x(Code M)
 No load current : 0.810-0.940/0.470 A
 Rated speed : 1765 rpm
 Slip : 1.94 %
 Rated torque : 0.982 ft.lb
 Locked rotor torque : 229 %
 Breakdown torque : 300 %
 Insulation class : F
 Service factor : 1.15
 Moment of inertia (J) : 0.0517 sq.ft.lb

Locked rotor time : 55s (cold) 31s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : -20°C to +40°C
 Altitude : 1000 m.a.s.l.
 Protection degree : IP55
 Cooling method : IC411 - TEFC
 Mounting : F-1
 Rotation¹ : Both (CW and CCW)
 Noise level² : 52.0 dB(A)
 Starting method : Direct On Line
 Approx. weight³ : 20.0 lb

Output	25%		50%		75%		100%	
Efficiency (%)	62.0	64.9	64.0	66.7	72.0	72.0	74.0	73.7
	61.1		63.6		70.2		73.1	
Power Factor	0.26	0.31	0.47	0.55	0.58	0.67	0.68	0.76
	0.26		0.48		0.60		0.69	

Foundation loads
 Max. traction : 27 lb
 Max. compression : 47 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6203 ZZ	6202 ZZ
Sealing	:	V'Ring	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
			Revision	