

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :																																																																																														
Product line		: W22 NEMA Premium Efficiency Three-Phase		Product code : 11431026																																																																																										
				Catalog # : 20018ET3E447T-W22																																																																																										
<table> <tr><td>Frame</td><td>:</td><td>445/7T</td><td>Locked rotor time</td><td>: 28s (cold) 16s (hot)</td></tr> <tr><td>Output</td><td>:</td><td>200 HP (150 kW)</td><td>Temperature rise</td><td>: 80 K</td></tr> <tr><td>Poles</td><td>:</td><td>4</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>:</td><td>60 Hz</td><td>Ambient temperature</td><td>: -20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>:</td><td>230/460 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>:</td><td>460/230 A</td><td>Protection degree</td><td>: IP55</td></tr> <tr><td>L. R. Amperes</td><td>:</td><td>3128/1564 A</td><td>Cooling method</td><td>: IC411 - TEFC</td></tr> <tr><td>LRC</td><td>:</td><td>6.8x(Code G)</td><td>Mounting</td><td>: F-1</td></tr> <tr><td>No load current</td><td>:</td><td>140/70.0 A</td><td>Rotation<sup>1</sup></td><td>: Both (CW and CCW)</td></tr> <tr><td>Rated speed</td><td>:</td><td>1785 rpm</td><td>Noise level<sup>2</sup></td><td>: 73.0 dB(A)</td></tr> <tr><td>Slip</td><td>:</td><td>0.83 %</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Rated torque</td><td>:</td><td>588 ft.lb</td><td>Approx. weight<sup>3</sup></td><td>: 2211 lb</td></tr> <tr><td>Locked rotor torque</td><td>:</td><td>229 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>:</td><td>250 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>:</td><td>F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>:</td><td>1.15</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>:</td><td>76.2 sq.ft.lb</td><td></td><td></td></tr> <tr><td>Design</td><td>:</td><td>B</td><td></td><td></td></tr> </table>				Frame	:	445/7T	Locked rotor time	: 28s (cold) 16s (hot)	Output	:	200 HP (150 kW)	Temperature rise	: 80 K	Poles	:	4	Duty cycle	: Cont.(S1)	Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C	Rated voltage	:	230/460 V	Altitude	: 1000 m.a.s.l.	Rated current	:	460/230 A	Protection degree	: IP55	L. R. Amperes	:	3128/1564 A	Cooling method	: IC411 - TEFC	LRC	:	6.8x(Code G)	Mounting	: F-1	No load current	:	140/70.0 A	Rotation <sup>1</sup>	: Both (CW and CCW)	Rated speed	:	1785 rpm	Noise level <sup>2</sup>	: 73.0 dB(A)	Slip	:	0.83 %	Starting method	: Direct On Line	Rated torque	:	588 ft.lb	Approx. weight <sup>3</sup>	: 2211 lb	Locked rotor torque	:	229 %			Breakdown torque	:	250 %			Insulation class	:	F			Service factor	:	1.15			Moment of inertia (J)	:	76.2 sq.ft.lb			Design	:	B			
Frame	:	445/7T	Locked rotor time	: 28s (cold) 16s (hot)																																																																																										
Output	:	200 HP (150 kW)	Temperature rise	: 80 K																																																																																										
Poles	:	4	Duty cycle	: Cont.(S1)																																																																																										
Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C																																																																																										
Rated voltage	:	230/460 V	Altitude	: 1000 m.a.s.l.																																																																																										
Rated current	:	460/230 A	Protection degree	: IP55																																																																																										
L. R. Amperes	:	3128/1564 A	Cooling method	: IC411 - TEFC																																																																																										
LRC	:	6.8x(Code G)	Mounting	: F-1																																																																																										
No load current	:	140/70.0 A	Rotation <sup>1</sup>	: Both (CW and CCW)																																																																																										
Rated speed	:	1785 rpm	Noise level <sup>2</sup>	: 73.0 dB(A)																																																																																										
Slip	:	0.83 %	Starting method	: Direct On Line																																																																																										
Rated torque	:	588 ft.lb	Approx. weight <sup>3</sup>	: 2211 lb																																																																																										
Locked rotor torque	:	229 %																																																																																												
Breakdown torque	:	250 %																																																																																												
Insulation class	:	F																																																																																												
Service factor	:	1.15																																																																																												
Moment of inertia (J)	:	76.2 sq.ft.lb																																																																																												
Design	:	B																																																																																												
Output	25%	50%	75%	100%	Foundation loads																																																																																									
Efficiency (%)	0.000	95.8	94.5	96.2	Max. traction	: 3435 lb																																																																																								
		95.0	95.0	95.4																																																																																										
Power Factor	0.00	0.73	0.78	0.82	Max. compression	: 5646 lb																																																																																								
		0.85	0.85	0.85																																																																																										
Losses at normative operating points (speed;torque), in percentage of rated output power																																																																																														
Losses (%)	P1 (0,9;1,0)	4.0	4.0	4.0	4.0																																																																																									
	P2 (0,5;1,0)	3.2	3.2	3.2	3.2																																																																																									
	P3 (0,25;1,0)	2.9	2.9	2.9	2.9																																																																																									
	P4 (0,9;0,5)	2.0	2.0	2.0	2.0																																																																																									
	P5 (0,5;0,5)	1.3	1.3	1.3	1.3																																																																																									
	P6 (0,5;0,25)	0.9	0.9	0.9	0.9																																																																																									
	P7 (0,25;0,25)	0.5	0.5	0.5	0.5																																																																																									
<table> <tr><td colspan="2" style="text-align: center;">Drive end</td><td colspan="3" style="text-align: center;">Non drive end</td></tr> <tr><td>Bearing type</td><td>:</td><td>6319 C3</td><td>6316 C3</td><td></td></tr> <tr><td>Sealing</td><td>:</td><td>WSeal</td><td>WSeal</td><td></td></tr> <tr><td>Lubrication interval</td><td>:</td><td>8000 h</td><td>10000 h</td><td></td></tr> <tr><td>Lubricant amount</td><td>:</td><td>45 g</td><td>34 g</td><td></td></tr> <tr><td>Lubricant type</td><td>:</td><td colspan="3" rowspan="3" style="text-align: center;">Mobil Polyrex EM</td></tr> </table>					Drive end		Non drive end			Bearing type	:	6319 C3	6316 C3		Sealing	:	WSeal	WSeal		Lubrication interval	:	8000 h	10000 h		Lubricant amount	:	45 g	34 g		Lubricant type	:	Mobil Polyrex EM																																																														
Drive end		Non drive end																																																																																												
Bearing type	:	6319 C3	6316 C3																																																																																											
Sealing	:	WSeal	WSeal																																																																																											
Lubrication interval	:	8000 h	10000 h																																																																																											
Lubricant amount	:	45 g	34 g																																																																																											
Lubricant type	:	Mobil Polyrex EM																																																																																												
Notes:																																																																																														
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>					These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																																																																									
Rev.	Changes Summary			Performed	Checked	Date																																																																																								
Performed by					Page	Revision																																																																																								
Checked by																																																																																														
Date	28/03/2024				1 / 1																																																																																									