## **DATA SHEET**

Date

28/03/2024



| Customer   | :  |   |        |   |   |  |                      |
|--|--|---|--------|---|---|--|----------------------|
| Product line   | : W22 NEMA Premium Efficiency Three<br>Phase |   |        | e- Product code :   |   | 11616141   |                      |
|  | Filase                                       | Filase  |        |   | Catalog # :   | 12536ET3H444TS-W22   |                      |
| Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque  |  | : 444/5TS<br>: 125 HP<br>: 2<br>: 60 Hz<br>: 575 V<br>: 107 A<br>: 708 A<br>: 6.6x(Code G)<br>: 27.2 A<br>: 3570 rpm<br>: 0.83 %<br>: 184 ft.lb<br>: 200 %<br>: 250 % |        | Catalog #:  Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³ |   | : 52s (cold) 29s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 81.0 dB(A) : Direct On Line : 1616 lb |                      |
| Insulation class Service factor  | :  |   |        |   |   |  |                      |
| Moment of inertial Design  | a (J) :                                      | 1.15<br>33.5 sq.ft.lb<br>B  |        |   |   |  |                      |
| Output   | 50%  | 75% 100%  | ,<br>0 | Foundation loads  |   |  |                      |
| Efficiency (%) 93.6  |  | 94.5 95.0   |        | Max. traction   |   | : 417 lb   |                      |
| Power Factor   | 0.82   | 0.87 0.89   |        | Max. cor  | npression   | : 2033 lb  |                      |
|  |  | ints (speed;torque),  |        |   |   |  |                      |
| P1 (0,9;1,0)<br>4.8  | P2 (0,5;1,0)<br>3.0                          | P3 (0,25;1,0)<br>2.5  |        | ),9;0,5)<br>3.1   | P5 (0,5;0,5)  | P6 (0,5;0,25)  | P7 (0,25;0,25<br>0.5 |
| Bearing type : Sealing : Lubrication interval : Lubricant amount : Lubricant type :  |  | <u>Drive end</u><br>6314 C3<br>WSeal<br>4000 h<br>27 g  |        | bil Polyrex   | Non drive end<br>6314 C3<br>WSeal<br>4000 h<br>27 g | <u>I</u>   |                      |
| Notes:   |  |   |        |   |   |  |                      |
| This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load. |  |   |        | These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.  |   |  |                      |
| Rev.   |  | Changes Summar  | ry     |   | Performed   | Checked  | Date                 |
|  |  | <u> </u>  |        |   |   |  |                      |
| Performed by<br>Checked by   |  |   |        |   | ı   | Page   | Revision             |
| Oliecked by  |  |   |        |   |   | <sub> </sub> raye  | L/GAI2IO[]           |

1/1