

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																							
Product line	: W22 High Efficiency Three-Phase		Product code :	13126112																			
Frame	: 324TSC	Locked rotor time	: 39s (cold) 22s (hot)																				
Output	: 40 HP (30 kW)	Temperature rise	: 80 K																				
Poles	: 2	Duty cycle	: Cont.(S1)																				
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C																				
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.																				
Rated current	: 93.4/46.7 A	Protection degree	: IP55																				
L. R. Amperes	: 588/294 A	Cooling method	: IC411 - TEFC																				
LRC	: 6.3x(Code G)	Mounting	: W-6																				
No load current	: 24.0/12.0 A	Rotation ¹	: Both (CW and CCW)																				
Rated speed	: 3555 rpm	Noise level ²	: 76.0 dB(A)																				
Slip	: 1.25 %	Starting method	: Direct On Line																				
Rated torque	: 59.1 ft.lb	Approx. weight ³	: 498 lb																				
Locked rotor torque	: 240 %																						
Breakdown torque	: 240 %																						
Insulation class	: F																						
Service factor	: 1.25																						
Moment of inertia (J)	: 4.90 sq.ft.lb																						
Design	: B																						
Output	25%	50%	75%	100%	Foundation loads																		
Efficiency (%)	90.8	92.3	91.0	91.7	91.7 90.2																		
	91.6	92.2	91.0	91.7	91.0 91.7 90.2 91.0																		
Power Factor	0.58	0.62	0.81	0.83	0.87 0.87 0.88 0.89																		
	0.60	0.58	0.83	0.82	0.88 0.86 0.89 0.88																		
Losses at normative operating points (speed;torque), in percentage of rated output power																							
Losses (%)	P1 (0,9;1,0)	8.6	10.3	10.3	9.4																		
	P2 (0,5;1,0)	6.6	8.0	8.0	7.2																		
	P3 (0,25;1,0)	5.8	7.0	7.0	6.4																		
	P4 (0,9;0,5)	4.3	5.2	5.2	4.7																		
	P5 (0,5;0,5)	2.5	3.0	3.0	2.7																		
	P6 (0,5;0,25)	1.5	1.8	1.8	1.7																		
	P7 (0,25;0,25)	0.9	1.1	1.1	1.0																		
<table> <thead> <tr> <th></th><th>Drive end</th><th>Non drive end</th></tr> </thead> <tbody> <tr> <td>Bearing type</td><td>: 6312 C3</td><td>6212 C3</td></tr> <tr> <td>Sealing</td><td>: V'Ring</td><td>V'Ring</td></tr> <tr> <td>Lubrication interval</td><td>: 6000 h</td><td>7000 h</td></tr> <tr> <td>Lubricant amount</td><td>: 21 g</td><td>13 g</td></tr> <tr> <td>Lubricant type</td><td colspan="3" rowspan="2">Mobil Polyrex EM</td></tr> </tbody> </table>						Drive end	Non drive end	Bearing type	: 6312 C3	6212 C3	Sealing	: V'Ring	V'Ring	Lubrication interval	: 6000 h	7000 h	Lubricant amount	: 21 g	13 g	Lubricant type	Mobil Polyrex EM		
	Drive end	Non drive end																					
Bearing type	: 6312 C3	6212 C3																					
Sealing	: V'Ring	V'Ring																					
Lubrication interval	: 6000 h	7000 h																					
Lubricant amount	: 21 g	13 g																					
Lubricant type	Mobil Polyrex EM																						
Notes:																							
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																				
Rev.	Changes Summary			Performed	Checked																		
Performed by					Page																		
Checked by					Revision																		
Date	29/03/2024				1 / 1																		
Customer :																							
Product line	: W22 High Efficiency Three-Phase		Product code :	13126112																			
Frame	: 324TSC	Locked rotor time	: 39s (cold) 22s (hot)																				
Output	: 40 HP (30 kW)	Temperature rise	: 80 K																				
Poles	: 2	Duty cycle	: Cont.(S1)																				
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C																				
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.																				
Rated current	: 93.4/46.7 A	Protection degree	: IP55																				
L. R. Amperes	: 588/294 A	Cooling method	: IC411 - TEFC																				
LRC	: 6.3x(Code G)	Mounting	: W-6																				
No load current	: 24.0/12.0 A	Rotation ¹	: Both (CW and CCW)																				
Rated speed	: 3555 rpm	Noise level ²	: 76.0 dB(A)																				
Slip	: 1.25 %	Starting method	: Direct On Line																				
Rated torque	: 59.1 ft.lb	Approx. weight ³	: 498 lb																				
Locked rotor torque	: 240 %																						
Breakdown torque	: 240 %																						
Insulation class	: F																						
Service factor	: 1.25																						
Moment of inertia (J)	: 4.90 sq.ft.lb																						
Design	: B																						
Output	25%	50%	75%	100%	Foundation loads																		
Efficiency (%)	90.8	92.3	91.0	91.7	91.7 90.2																		
	91.6	92.2	91.0	91.7	91.0 91.7 90.2 91.0																		
Power Factor	0.58	0.62	0.81	0.83	0.87 0.87 0.88 0.89																		
	0.60	0.58	0.83	0.82	0.88 0.86 0.89 0.88																		
Losses at normative operating points (speed;torque), in percentage of rated output power																							
Losses (%)	P1 (0,9;1,0)	8.6	10.3	10.3	9.4																		
	P2 (0,5;1,0)	6.6	8.0	8.0	7.2																		
	P3 (0,25;1,0)	5.8	7.0	7.0	6.4																		
	P4 (0,9;0,5)	4.3	5.2	5.2	4.7																		
	P5 (0,5;0,5)	2.5	3.0	3.0	2.7																		
	P6 (0,5;0,25)	1.5	1.8	1.8	1.7																		
	P7 (0,25;0,25)	0.9	1.1	1.1	1.0																		
<table> <thead> <tr> <th></th><th>Drive end</th><th>Non drive end</th></tr> </thead> <tbody> <tr> <td>Bearing type</td><td>: 6312 C3</td><td>6212 C3</td></tr> <tr> <td>Sealing</td><td>: V'Ring</td><td>V'Ring</td></tr> <tr> <td>Lubrication interval</td><td>: 6000 h</td><td>7000 h</td></tr> <tr> <td>Lubricant amount</td><td>: 21 g</td><td>13 g</td></tr> <tr> <td>Lubricant type</td><td colspan="3" rowspan="2">Mobil Polyrex EM</td></tr> </tbody> </table>						Drive end	Non drive end	Bearing type	: 6312 C3	6212 C3	Sealing	: V'Ring	V'Ring	Lubrication interval	: 6000 h	7000 h	Lubricant amount	: 21 g	13 g	Lubricant type	Mobil Polyrex EM		
	Drive end	Non drive end																					
Bearing type	: 6312 C3	6212 C3																					
Sealing	: V'Ring	V'Ring																					
Lubrication interval	: 6000 h	7000 h																					
Lubricant amount	: 21 g	13 g																					
Lubricant type	Mobil Polyrex EM																						
Notes:																							
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																				
Rev.	Changes Summary			Performed	Checked																		
Performed by					Page																		
Checked by					Revision																		
Date	29/03/2024				1 / 1																		