

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																												
Product line	: W22 NEMA Premium Efficiency Three-Phase			Product code :	11165695																							
				Catalog # :	06036ET3H364TS-W22																							
Frame	: 364/5TS	Locked rotor time	: 25s (cold) 14s (hot)																									
Output	: 60 HP (45 kW)	Temperature rise	: 80 K																									
Poles	: 2	Duty cycle	: Cont.(S1)																									
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C																									
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.																									
Rated current	: 53.6 A	Protection degree	: IP55																									
L. R. Amperes	: 354 A	Cooling method	: IC411 - TEFC																									
LRC	: 6.6x(Code G)	Mounting	: F-1																									
No load current	: 12.8 A	Rotation ¹	: Both (CW and CCW)																									
Rated speed	: 3555 rpm	Noise level ²	: 79.0 dB(A)																									
Slip	: 1.25 %	Starting method	: Direct On Line																									
Rated torque	: 88.6 ft.lb	Approx. weight ³	: 846 lb																									
Locked rotor torque	: 200 %																											
Breakdown torque	: 260 %																											
Insulation class	: F																											
Service factor	: 1.25																											
Moment of inertia (J)	: 10.6 sq.ft.lb																											
Design	: B																											
Output	25%	50%	75%	100%	Foundation loads																							
Efficiency (%)	91.0	91.7	93.0	93.6	Max. traction	: 365 lb																						
Power Factor	0.59	0.81	0.88	0.90	Max. compression	: 1212 lb																						
Losses at normative operating points (speed;torque), in percentage of rated output power																												
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)																						
6.3	4.7	4.4	3.3	1.7	1.1	0.6																						
<table> <thead> <tr> <th></th><th>Drive end</th><th>Non drive end</th></tr> </thead> <tbody> <tr> <td>Bearing type</td><td>: 6314 C3</td><td>: 6314 C3</td></tr> <tr> <td>Sealing</td><td>: WSeal</td><td>: WSeal</td></tr> <tr> <td>Lubrication interval</td><td>: 4000 h</td><td>: 4000 h</td></tr> <tr> <td>Lubricant amount</td><td>: 27 g</td><td>: 27 g</td></tr> <tr> <td>Lubricant type</td><td colspan="3" rowspan="3">: Mobil Polyrex EM</td><td></td><td></td><td></td></tr> </tbody></table>								Drive end	Non drive end	Bearing type	: 6314 C3	: 6314 C3	Sealing	: WSeal	: WSeal	Lubrication interval	: 4000 h	: 4000 h	Lubricant amount	: 27 g	: 27 g	Lubricant type	: Mobil Polyrex EM					
	Drive end	Non drive end																										
Bearing type	: 6314 C3	: 6314 C3																										
Sealing	: WSeal	: WSeal																										
Lubrication interval	: 4000 h	: 4000 h																										
Lubricant amount	: 27 g	: 27 g																										
Lubricant type	: Mobil Polyrex EM																											
Notes:																												
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>				<p>These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.</p>																								
Rev.	Changes Summary			Performed	Checked	Date																						
Performed by					Page	Revision																						
Checked by																												
Date	29/03/2024				1 / 1																							
Customer :																												
Product line	: W22 NEMA Premium Efficiency Three-Phase			Product code :	11165695																							
				Catalog # :	06036ET3H364TS-W22																							
Frame	: 364/5TS	Locked rotor time	: 25s (cold) 14s (hot)																									
Output	: 60 HP (45 kW)	Temperature rise	: 80 K																									
Poles	: 2	Duty cycle	: Cont.(S1)																									
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C																									
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.																									
Rated current	: 53.6 A	Protection degree	: IP55																									
L. R. Amperes	: 354 A	Cooling method	: IC411 - TEFC																									
LRC	: 6.6x(Code G)	Mounting	: F-1																									
No load current	: 12.8 A	Rotation ¹	: Both (CW and CCW)																									
Rated speed	: 3555 rpm	Noise level ²	: 79.0 dB(A)																									
Slip	: 1.25 %	Starting method	: Direct On Line																									
Rated torque	: 88.6 ft.lb	Approx. weight ³	: 846 lb																									
Locked rotor torque	: 200 %																											
Breakdown torque	: 260 %																											
Insulation class	: F																											
Service factor	: 1.25																											
Moment of inertia (J)	: 10.6 sq.ft.lb																											
Design	: B																											
Output	25%	50%	75%	100%	Foundation loads																							
Efficiency (%)	91.0	91.7	93.0	93.6	Max. traction	: 365 lb																						
Power Factor	0.59	0.81	0.88	0.90	Max. compression	: 1212 lb																						
Losses at normative operating points (speed;torque), in percentage of rated output power																												
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)																						
6.3	4.7	4.4	3.3	1.7	1.1	0.6																						
<table> <thead> <tr> <th></th><th>Drive end</th><th>Non drive end</th></tr> </thead> <tbody> <tr> <td>Bearing type</td><td>: 6314 C3</td><td>: 6314 C3</td></tr> <tr> <td>Sealing</td><td>: WSeal</td><td>: WSeal</td></tr> <tr> <td>Lubrication interval</td><td>: 4000 h</td><td>: 4000 h</td></tr> <tr> <td>Lubricant amount</td><td>: 27 g</td><td>: 27 g</td></tr> <tr> <td>Lubricant type</td><td colspan="3" rowspan="3">: Mobil Polyrex EM</td><td></td><td></td><td></td></tr> </tbody></table>								Drive end	Non drive end	Bearing type	: 6314 C3	: 6314 C3	Sealing	: WSeal	: WSeal	Lubrication interval	: 4000 h	: 4000 h	Lubricant amount	: 27 g	: 27 g	Lubricant type	: Mobil Polyrex EM					
	Drive end	Non drive end																										
Bearing type	: 6314 C3	: 6314 C3																										
Sealing	: WSeal	: WSeal																										
Lubrication interval	: 4000 h	: 4000 h																										
Lubricant amount	: 27 g	: 27 g																										
Lubricant type	: Mobil Polyrex EM																											
Notes:																												
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>				<p>These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.</p>																								
Rev.	Changes Summary			Performed	Checked	Date																						
Performed by					Page	Revision																						
Checked by																												
Date	29/03/2024				1 / 1																							