

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12445718

Catalog # : 00156ET3H143T-W22

Frame	: 143/5T	Locked rotor time	: 37s (cold) 21s (hot)
Output	: 1.5 HP (1.1 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 1.57 A	Protection degree	: IP55
L. R. Amperes	: 14.0 A	Cooling method	: IC411 - TEFC
LRC	: 8.9x(Code L)	Mounting	: F-1
No load current	: 0.664 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 3480 rpm	Noise level <sup>2</sup>	: 68.0 dB(A)
Slip	: 3.33 %	Starting method	: Direct On Line
Rated torque	: 2.26 ft.lb	Approx. weight <sup>3</sup>	: 44.2 lb
Locked rotor torque	: 310 %		
Breakdown torque	: 370 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0470 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%
Efficiency (%)	81.1	81.5	84.0	84.0
Power Factor	0.43	0.68	0.78	0.84

Foundation loads

Max. traction : 50 lb  
Max. compression : 95 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
17.7	13.3	12.1	9.8	5.6	3.8	2.4

### Drive end

### Non drive end

Bearing type	:	6205 ZZ	6204 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	26/03/2024			
			Page	Revision
			1 / 1	