

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 13468368

Catalog # : 00336ET3ER145TC-W22

Frame	: 145TC	Locked rotor time	: 25s (cold) 14s (hot)
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 7.42/3.71 A	Protection degree	: IP55
L. R. Amperes	: 60.1/30.1 A	Cooling method	: IC411 - TEFC
LRC	: 8.1x(Code J)	Mounting	: W-6
No load current	: 2.60/1.30 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3460 rpm	Noise level ²	: 68.0 dB(A)
Slip	: 3.89 %	Starting method	: Direct On Line
Rated torque	: 4.55 ft.lb	Approx. weight ³	: 53.3 lb
Locked rotor torque	: 330 %		
Breakdown torque	: 360 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0605 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads					
Efficiency (%)	85.2	80.8	85.5	81.9	86.5	84.0	86.5	84.8	Max. traction	: 132 lb
	80.9	80.9	82.0	82.2	84.4	84.8	85.3	85.9		
	83.9	84.0	84.0	84.5	85.0	85.5	84.6	85.6		
	84.4	85.0	86.0	86.2						
Power Factor	0.47	0.41	0.70	0.63	0.81	0.76	0.86	0.83	Max. compression	: 185 lb
	0.37	0.34	0.58	0.55	0.72	0.69	0.80	0.77		
	0.54	0.49	0.76	0.72	0.85	0.82	0.89	0.87		
	0.45	0.69	0.80	0.86						

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	14.8	14.8	14.8	14.8	14.8	14.8	14.8
	P2 (0,5;1,0)	12.3	12.3	12.3	12.3	12.3	12.3	12.3
	P3 (0,25;1,0)	11.7	11.7	11.7	11.7	11.7	11.7	11.7
	P4 (0,9;0,5)	6.8	6.8	6.8	6.8	6.8	6.8	6.8
	P5 (0,5;0,5)	4.3	4.3	4.3	4.3	4.3	4.3	4.3
	P6 (0,5;0,25)	2.6	2.6	2.6	2.6	2.6	2.6	2.6
	P7 (0,25;0,25)	1.7	1.7	1.7	1.7	1.7	1.7	1.7

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6205 ZZ	6204 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/03/2024			
			Page	Revision
			1 / 1	