

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																																																
Product line	: W22 NEMA Premium Efficiency Three-Phase			Product code :	12445723																																											
				Catalog # :	00312ET3H213T-W22																																											
Frame	: 213/5T	Locked rotor time	: 104s (cold) 58s (hot)																																													
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K																																													
Poles	: 6	Duty cycle	: Cont.(S1)																																													
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C																																													
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.																																													
Rated current	: 3.53 A	Protection degree	: IP55																																													
L. R. Amperes	: 24.7 A	Cooling method	: IC411 - TEFC																																													
LRC	: 7.0x(Code K)	Mounting	: F-1																																													
No load current	: 2.20 A	Rotation ¹	: Both (CW and CCW)																																													
Rated speed	: 1175 rpm	Noise level ²	: 55.0 dB(A)																																													
Slip	: 2.08 %	Starting method	: Direct On Line																																													
Rated torque	: 13.4 ft.lb	Approx. weight ³	: 155 lb																																													
Locked rotor torque	: 200 %																																															
Breakdown torque	: 280 %																																															
Insulation class	: F																																															
Service factor	: 1.25																																															
Moment of inertia (J)	: 1.20 sq.ft.lb																																															
Design	: B																																															
Output	50%	75%	100%	Foundation loads																																												
Efficiency (%)	86.5	88.5	89.5	Max. traction	: 134 lb																																											
Power Factor	0.50	0.63	0.70	Max. compression	: 289 lb																																											
Losses at normative operating points (speed;torque), in percentage of rated output power																																																
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)																																										
11.0	8.5	7.7	6.7	4.4	3.4	2.5																																										
<table border="0"> <tr> <td colspan="4" style="text-align: center;">Drive end</td><td colspan="3" style="text-align: center;">Non drive end</td></tr> <tr> <td>Bearing type</td><td>:</td><td colspan="2">6308 ZZ</td><td colspan="3" style="text-align: center;">6207 ZZ</td></tr> <tr> <td>Sealing</td><td>:</td><td colspan="2">V'Ring</td><td colspan="3" style="text-align: center;">V'Ring</td></tr> <tr> <td>Lubrication interval</td><td>:</td><td colspan="2">-</td><td colspan="3" style="text-align: center;">-</td></tr> <tr> <td>Lubricant amount</td><td>:</td><td colspan="2">-</td><td colspan="3" rowspan="3" style="text-align: center;">-</td></tr> <tr> <td>Lubricant type</td><td>:</td><td colspan="5" rowspan="2" style="text-align: center;">Mobil Polyrex EM</td></tr> </table>							Drive end				Non drive end			Bearing type	:	6308 ZZ		6207 ZZ			Sealing	:	V'Ring		V'Ring			Lubrication interval	:	-		-			Lubricant amount	:	-		-			Lubricant type	:	Mobil Polyrex EM				
Drive end				Non drive end																																												
Bearing type	:	6308 ZZ		6207 ZZ																																												
Sealing	:	V'Ring		V'Ring																																												
Lubrication interval	:	-		-																																												
Lubricant amount	:	-		-																																												
Lubricant type	:	Mobil Polyrex EM																																														
Notes:																																																
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																												
Rev.	Changes Summary			Performed	Checked	Date																																										
Performed by					Page	Revision																																										
Checked by																																																
Date	28/03/2024				1 / 1																																											