

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Standard Efficiency Three-Phase

Product code :

12686366

Catalog # :

01512ES3EOW284T-W22

Frame	: 284/6T	Locked rotor time	: 28s (cold) 16s (hot)
Output	: 15 HP (11 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 40.5-36.6/18.3 A	Protection degree	: IP55
L. R. Amperes	: 247-223/112 A	Cooling method	: IC411 - TEFC
LRC	: 6.1x(Code G)	Mounting	: F-2
No load current	: 12.2-11.0/5.50 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1110 rpm	Noise level ²	: 59.0 dB(A)
Slip	: 7.50 %	Starting method	: Direct On Line
Rated torque	: 71.0 ft.lb	Approx. weight ³	: 408 lb
Locked rotor torque	: 300 %		
Breakdown torque	: 0 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 7.69 sq.ft.lb		
Design	: D		

Output	25%	50%	75%	100%
Efficiency (%)	85.7	85.5	86.5	85.5
Power Factor	0.54	0.78	0.85	0.88

Foundation loads	
Max. traction	: -204 lb
Max. compression	: 204 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6311 C3	6211 C3
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	18 g	11 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	26/03/2024			
			Revision	