

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 14387119

Catalog # : 02018ET3HR256TC-W22

Frame : 256TC
Output : 20 HP (15 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 575 V
Rated current : 19.3 A
L. R. Amperes : 133 A
LRC : 6.9x(Code H)
No load current : 7.68 A
Rated speed : 1770 rpm
Slip : 1.67 %
Rated torque : 59.3 ft.lb
Locked rotor torque : 240 %
Breakdown torque : 260 %
Insulation class : F
Service factor : 1.25
Moment of inertia (J) : 3.10 sq.ft.lb
Design : B

Locked rotor time : 54s (cold) 30s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 64.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 329 lb

Output 25% 50% 75% 100%

Efficiency (%) 91.0 91.7 92.4 93.0
Power Factor 0.43 0.68 0.79 0.84

Foundation loads

Max. traction : 575 lb
Max. compression : 905 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
7.5	6.4	5.8	3.6	2.5	1.6	1.1

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6309 C3	6209 C3
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	13 g	9 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/03/2024			
			Page	Revision
			1 / 1	