

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																												
Product line	: W22 NEMA Premium Efficiency Three-Phase			Product code :	11611018																							
				Catalog # :	00212ET3H184T-W22																							
Frame	: 182/4T	Locked rotor time	: 55s (cold) 31s (hot)																									
Output	: 2 HP (1.5 kW)	Temperature rise	: 80 K																									
Poles	: 6	Duty cycle	: Cont.(S1)																									
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C																									
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.																									
Rated current	: 2.58 A	Protection degree	: IP55																									
L. R. Amperes	: 19.3 A	Cooling method	: IC411 - TEFC																									
LRC	: 7.5x(Code L)	Mounting	: F-1																									
No load current	: 1.52 A	Rotation ¹	: Both (CW and CCW)																									
Rated speed	: 1170 rpm	Noise level ²	: 52.0 dB(A)																									
Slip	: 2.50 %	Starting method	: Direct On Line																									
Rated torque	: 8.98 ft.lb	Approx. weight ³	: 97.5 lb																									
Locked rotor torque	: 300 %																											
Breakdown torque	: 350 %																											
Insulation class	: F																											
Service factor	: 1.25																											
Moment of inertia (J)	: 0.6210 sq.ft.lb																											
Design	: B																											
Output	50%	75%	100%	Foundation loads																								
Efficiency (%)	86.5	87.5	88.5	Max. traction	: 152 lb																							
Power Factor	0.46	0.58	0.66	Max. compression	: 249 lb																							
Losses at normative operating points (speed;torque), in percentage of rated output power																												
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)																						
12.3	9.8	9.2	7.4	5.0	3.9	2.9																						
<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;"></th><th style="width: 50%;">Drive end</th><th style="width: 50%;">Non drive end</th></tr> </thead> <tbody> <tr> <td>Bearing type</td><td>: 6207 ZZ</td><td>: 6206 ZZ</td></tr> <tr> <td>Sealing</td><td>: V'Ring</td><td>: V'Ring</td></tr> <tr> <td>Lubrication interval</td><td>: -</td><td>: -</td></tr> <tr> <td>Lubricant amount</td><td>: -</td><td>: -</td></tr> <tr> <td>Lubricant type</td><td colspan="3" rowspan="3">: Mobil Polyrex EM</td><td colspan="3" rowspan="2"></td></tr> </tbody></table>								Drive end	Non drive end	Bearing type	: 6207 ZZ	: 6206 ZZ	Sealing	: V'Ring	: V'Ring	Lubrication interval	: -	: -	Lubricant amount	: -	: -	Lubricant type	: Mobil Polyrex EM					
	Drive end	Non drive end																										
Bearing type	: 6207 ZZ	: 6206 ZZ																										
Sealing	: V'Ring	: V'Ring																										
Lubrication interval	: -	: -																										
Lubricant amount	: -	: -																										
Lubricant type	: Mobil Polyrex EM																											
Notes:																												
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																								
Rev.	Changes Summary			Performed	Checked	Date																						
Performed by					Page	Revision																						
Checked by																												
Date	28/03/2024				1 / 1																							
Customer :																												
Product line	: W22 NEMA Premium Efficiency Three-Phase			Product code :	11611018																							
				Catalog # :	00212ET3H184T-W22																							
Frame	: 182/4T	Locked rotor time	: 55s (cold) 31s (hot)																									
Output	: 2 HP (1.5 kW)	Temperature rise	: 80 K																									
Poles	: 6	Duty cycle	: Cont.(S1)																									
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C																									
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.																									
Rated current	: 2.58 A	Protection degree	: IP55																									
L. R. Amperes	: 19.3 A	Cooling method	: IC411 - TEFC																									
LRC	: 7.5x(Code L)	Mounting	: F-1																									
No load current	: 1.52 A	Rotation ¹	: Both (CW and CCW)																									
Rated speed	: 1170 rpm	Noise level ²	: 52.0 dB(A)																									
Slip	: 2.50 %	Starting method	: Direct On Line																									
Rated torque	: 8.98 ft.lb	Approx. weight ³	: 97.5 lb																									
Locked rotor torque	: 300 %																											
Breakdown torque	: 350 %																											
Insulation class	: F																											
Service factor	: 1.25																											
Moment of inertia (J)	: 0.6210 sq.ft.lb																											
Design	: B																											
Output	50%	75%	100%	Foundation loads																								
Efficiency (%)	86.5	87.5	88.5	Max. traction	: 152 lb																							
Power Factor	0.46	0.58	0.66	Max. compression	: 249 lb																							
Losses at normative operating points (speed;torque), in percentage of rated output power																												
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)																						
12.3	9.8	9.2	7.4	5.0	3.9	2.9																						
<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">Drive end</th><th style="width: 50%;">Non drive end</th></tr> </thead> <tbody> <tr> <td>Bearing type</td><td>: 6207 ZZ</td></tr> <tr> <td>Sealing</td><td>: V'Ring</td></tr> <tr> <td>Lubrication interval</td><td>: -</td></tr> <tr> <td>Lubricant amount</td><td>: -</td></tr> <tr> <td>Lubricant type</td><td colspan="3" rowspan="3">: Mobil Polyrex EM</td><td colspan="3" rowspan="2"></td></tr> </tbody> </table>							Drive end	Non drive end	Bearing type	: 6207 ZZ	Sealing	: V'Ring	Lubrication interval	: -	Lubricant amount	: -	Lubricant type	: Mobil Polyrex EM										
Drive end	Non drive end																											
Bearing type	: 6207 ZZ																											
Sealing	: V'Ring																											
Lubrication interval	: -																											
Lubricant amount	: -																											
Lubricant type	: Mobil Polyrex EM																											
Notes:																												
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																								
Rev.	Changes Summary			Performed	Checked	Date																						
Performed by					Page	Revision																						
Checked by																												
Date	28/03/2024				1 / 1																							