

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12054597

Catalog # : 03018ET3P286T-W22

Frame : 284/6T  
Output : 30 HP (22 kW)  
Poles : 4  
Frequency : 60 Hz  
Rated voltage : 200 V  
Rated current : 80.7 A  
L. R. Amperes : 492 A  
LRC : 6.1x(Code G)  
No load current : 28.3 A  
Rated speed : 1770 rpm  
Slip : 1.67 %  
Rated torque : 89.0 ft.lb  
Locked rotor torque : 240 %  
Breakdown torque : 240 %  
Insulation class : F  
Service factor : 1.25  
Moment of inertia (J) : 5.85 sq.ft.lb  
Design : B

Locked rotor time : 36s (cold) 20s (hot)  
Temperature rise : 80 K  
Duty cycle : Cont.(S1)  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Protection degree : IP55  
Cooling method : IC411 - TEFC  
Mounting : F-1  
Rotation<sup>1</sup> : Both (CW and CCW)  
Noise level<sup>2</sup> : 63.0 dB(A)  
Starting method : Direct On Line  
Approx. weight<sup>3</sup> : 467 lb

Output 25% 50% 75% 100%

Efficiency (%) 92.3 93.0 93.0 93.6  
Power Factor 0.46 0.70 0.80 0.84

Foundation loads

Max. traction : 698 lb  
Max. compression : 1165 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
6.8	5.8	5.2	3.1	2.2	1.4	0.9

	Drive end	Non drive end
Bearing type :	6311 C3	6211 C3
Sealing :	V'Ring	V'Ring
Lubrication interval :	20000 h	20000 h
Lubricant amount :	18 g	11 g
Lubricant type :	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/03/2024			

Page 1 / 1  
Revision