

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12445771

Catalog # : 00336ET3H182TC-W22

Frame	: 182/4TC	Locked rotor time	: 46s (cold) 26s (hot)
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 3.01 A	Protection degree	: IP55
L. R. Amperes	: 25.9 A	Cooling method	: IC411 - TEFC
LRC	: 8.6x(Code K)	Mounting	: F-1
No load current	: 1.28 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3515 rpm	Noise level ²	: 66.0 dB(A)
Slip	: 2.36 %	Starting method	: Direct On Line
Rated torque	: 4.48 ft.lb	Approx. weight ³	: 80.4 lb
Locked rotor torque	: 250 %		
Breakdown torque	: 380 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.1889 sq.ft.lb		
Design	: B		

Output 25% 50% 75% 100%

Efficiency (%) 81.1 82.0 86.0 86.5

Power Factor 0.44 0.70 0.80 0.85

Foundation loads

: 68 lb

Max. traction

: 149 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
14.6	10.7	9.4	8.3	4.5	3.1	1.8

Drive end

Non drive end

Bearing type : 6207 ZZ

6206 ZZ

Sealing : V'Ring

V'Ring

Lubrication interval : -

-

Lubricant amount : -

-

Lubricant type : Mobil Polyrex EM

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/03/2024			
			Page	Revision
			1 / 1	