

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :						
Product line	: Rolled Steel NEMA Premium Efficiency Three-Phase		Product code :	13187814		
			Catalog # :	00152ET3E182TC-S		
Frame	: 182/4TC	Locked rotor time	: 99s (cold) 55s (hot)			
Output	: 1.5 HP (1.1 kW)	Temperature rise	: 80 K			
Poles	: 6	Duty cycle	: Cont.(S1)			
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C			
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.			
Rated current	: 4.44/2.22 A	Protection degree	: IP55			
L. R. Amperes	: 30.6/15.3 A	Cooling method	: IC411 - TEFC			
LRC	: 6.9x(Code K)	Mounting	: F-1			
No load current	: 2.73/1.36 A	Rotation ¹	: Both (CW and CCW)			
Rated speed	: 1170 rpm	Noise level ²	: 52.0 dB(A)			
Slip	: 2.50 %	Starting method	: Direct On Line			
Rated torque	: 6.73 ft.lb	Approx. weight ³	: 78.0 lb			
Locked rotor torque	: 240 %					
Breakdown torque	: 340 %					
Insulation class	: F					
Service factor	: 1.15					
Moment of inertia (J)	: 0.2800 sq.ft.lb					
Design	: B					
Output	25%	50%	75%	100%		
Efficiency (%)	82.8	84.4	84.0	84.2		
	82.3	82.9	85.3	85.5		
Power Factor	0.29	0.34	0.50	0.58		
	0.29	0.51	0.63	0.72		
Foundation loads						
	Max. traction		: 133 lb			
	Max. compression		: 211 lb			
Drive end						
Bearing type	: 6206 ZZ	6205 ZZ				
Sealing	: V'Ring	Without Bearing Seal				
Lubrication interval	: -	-				
Lubricant amount	: -	-				
Lubricant type	: Mobil Polyrex EM					
Notes:						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.						
These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.						
Rev.	Changes Summary			Performed		
				Checked		
Performed by						
Checked by						
Date	26/03/2024					
		Page	Revision			
		1 / 1				