

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																																																																																														
Product line		: W22 NEMA Premium Efficiency Three-Phase		Product code : 12134320																																																																																										
				Catalog # : 30012ET3GRB449T-W22																																																																																										
<table> <tr><td>Frame</td><td>:</td><td>447/9T</td><td>Locked rotor time</td><td>: 18s (cold) 10s (hot)</td></tr> <tr><td>Output</td><td>:</td><td>300 HP (220 kW)</td><td>Temperature rise</td><td>: 80 K</td></tr> <tr><td>Poles</td><td>:</td><td>6</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>:</td><td>60 Hz</td><td>Ambient temperature</td><td>: -20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>:</td><td>460 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>:</td><td>356 A</td><td>Protection degree</td><td>: IP55</td></tr> <tr><td>L. R. Amperes</td><td>:</td><td>2741 A</td><td>Cooling method</td><td>: IC411 - TEFC</td></tr> <tr><td>LRC</td><td>:</td><td>7.7x(Code J)</td><td>Mounting</td><td>: F-1</td></tr> <tr><td>No load current</td><td>:</td><td>170 A</td><td>Rotation¹</td><td>: Both (CW and CCW)</td></tr> <tr><td>Rated speed</td><td>:</td><td>1189 rpm</td><td>Noise level²</td><td>: 70.0 dB(A)</td></tr> <tr><td>Slip</td><td>:</td><td>0.92 %</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Rated torque</td><td>:</td><td>1320 ft.lb</td><td>Approx. weight³</td><td>: 3115 lb</td></tr> <tr><td>Locked rotor torque</td><td>:</td><td>270 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>:</td><td>300 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>:</td><td>F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>:</td><td>1.00</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>:</td><td>145 sq.ft.lb</td><td></td><td></td></tr> <tr><td>Design</td><td>:</td><td>A</td><td></td><td></td></tr> </table>				Frame	:	447/9T	Locked rotor time	: 18s (cold) 10s (hot)	Output	:	300 HP (220 kW)	Temperature rise	: 80 K	Poles	:	6	Duty cycle	: Cont.(S1)	Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C	Rated voltage	:	460 V	Altitude	: 1000 m.a.s.l.	Rated current	:	356 A	Protection degree	: IP55	L. R. Amperes	:	2741 A	Cooling method	: IC411 - TEFC	LRC	:	7.7x(Code J)	Mounting	: F-1	No load current	:	170 A	Rotation ¹	: Both (CW and CCW)	Rated speed	:	1189 rpm	Noise level ²	: 70.0 dB(A)	Slip	:	0.92 %	Starting method	: Direct On Line	Rated torque	:	1320 ft.lb	Approx. weight ³	: 3115 lb	Locked rotor torque	:	270 %			Breakdown torque	:	300 %			Insulation class	:	F			Service factor	:	1.00			Moment of inertia (J)	:	145 sq.ft.lb			Design	:	A			
Frame	:	447/9T	Locked rotor time	: 18s (cold) 10s (hot)																																																																																										
Output	:	300 HP (220 kW)	Temperature rise	: 80 K																																																																																										
Poles	:	6	Duty cycle	: Cont.(S1)																																																																																										
Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C																																																																																										
Rated voltage	:	460 V	Altitude	: 1000 m.a.s.l.																																																																																										
Rated current	:	356 A	Protection degree	: IP55																																																																																										
L. R. Amperes	:	2741 A	Cooling method	: IC411 - TEFC																																																																																										
LRC	:	7.7x(Code J)	Mounting	: F-1																																																																																										
No load current	:	170 A	Rotation ¹	: Both (CW and CCW)																																																																																										
Rated speed	:	1189 rpm	Noise level ²	: 70.0 dB(A)																																																																																										
Slip	:	0.92 %	Starting method	: Direct On Line																																																																																										
Rated torque	:	1320 ft.lb	Approx. weight ³	: 3115 lb																																																																																										
Locked rotor torque	:	270 %																																																																																												
Breakdown torque	:	300 %																																																																																												
Insulation class	:	F																																																																																												
Service factor	:	1.00																																																																																												
Moment of inertia (J)	:	145 sq.ft.lb																																																																																												
Design	:	A																																																																																												
Output	25%	50%	75%	100%	Foundation loads																																																																																									
Efficiency (%)	95.3	94.5	95.4	95.0	Max. traction : 8695 lb																																																																																									
	94.0	93.3	94.5	94.1	Max. compression : 11810 lb																																																																																									
Power Factor	0.38	0.37	0.63	0.61																																																																																										
	0.35	0.32	0.59	0.56																																																																																										
Losses at normative operating points (speed;torque), in percentage of rated output power																																																																																														
Losses (%)	P1 (0,9;1,0)	5.2	5.2	5.2	5.2																																																																																									
	P2 (0,5;1,0)	4.3	4.3	4.3	4.3																																																																																									
	P3 (0,25;1,0)	3.7	3.7	3.7	3.7																																																																																									
	P4 (0,9;0,5)	3.0	3.0	3.0	3.0																																																																																									
	P5 (0,5;0,5)	2.3	2.3	2.3	2.3																																																																																									
	P6 (0,5;0,25)	1.8	1.8	1.8	1.8																																																																																									
	P7 (0,25;0,25)	1.1	1.1	1.1	1.1																																																																																									
<table> <tr><td colspan="2">Bearings</td><td>Drive end</td><td>Non drive end</td><td></td></tr> <tr><td>Bearing type</td><td>:</td><td>NU-322 C3</td><td>6319 C3</td><td></td></tr> <tr><td>Sealing</td><td>:</td><td>WSeal</td><td>WSeal</td><td></td></tr> <tr><td>Lubrication interval</td><td>:</td><td>7000 h</td><td>13000 h</td><td></td></tr> <tr><td>Lubricant amount</td><td>:</td><td>60 g</td><td>45 g</td><td></td></tr> <tr><td>Lubricant type</td><td>:</td><td colspan="3" rowspan="3">Mobil Polyrex EM</td></tr> </table>					Bearings		Drive end	Non drive end		Bearing type	:	NU-322 C3	6319 C3		Sealing	:	WSeal	WSeal		Lubrication interval	:	7000 h	13000 h		Lubricant amount	:	60 g	45 g		Lubricant type	:	Mobil Polyrex EM																																																														
Bearings		Drive end	Non drive end																																																																																											
Bearing type	:	NU-322 C3	6319 C3																																																																																											
Sealing	:	WSeal	WSeal																																																																																											
Lubrication interval	:	7000 h	13000 h																																																																																											
Lubricant amount	:	60 g	45 g																																																																																											
Lubricant type	:	Mobil Polyrex EM																																																																																												
Notes:																																																																																														
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>					These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																																																																									
Rev.	Changes Summary			Performed	Checked	Date																																																																																								
Performed by					Page		Revision																																																																																							
Checked by																																																																																														
Date	28/03/2024																																																																																													