

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12113286

Catalog # : 07518ET3H365TSCF2-W2

Frame	: 364/5TSC	Locked rotor time	: 25s (cold) 14s (hot)
Output	: 75 HP (55 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 69.8 A	Protection degree	: IP55
L. R. Amperes	: 446 A	Cooling method	: IC411 - TEFC
LRC	: 6.4x(Code G)	Mounting	: F-2
No load current	: 26.4 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1780 rpm	Noise level ²	: 67.0 dB(A)
Slip	: 1.11 %	Starting method	: Direct On Line
Rated torque	: 221 ft.lb	Approx. weight ³	: 937 lb
Locked rotor torque	: 240 %		
Breakdown torque	: 260 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 23.3 sq.ft.lb		
Design	: B		

Output 25% 50% 75% 100%

Foundation loads

Efficiency (%) 94.0 94.5 95.0 95.4

Max. traction : 1501 lb

Power Factor 0.44 0.68 0.78 0.83

Max. compression : 2438 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
4.7	3.8	3.5	2.4	1.6	1.1	0.7

Drive end

Non drive end

Bearing type	:	6314 C3	6314 C3
Sealing	:	Lip Seal	Lip Seal
Lubrication interval	:	12000 h	12000 h
Lubricant amount	:	27 g	27 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/03/2024			
			Page	Revision
			1 / 1	